



PART NUMBER	SEALING RANGE	BODY BORE
RSM-25203	.125 - .188	.800
RSM-25204	.188 - .250	.800
RSM-25205	.250 - .312	.800
RSM-25206	.312 - .375	.800
RSM-25207	.375 - .437	.800
RSM-25208	.438 - .500	.800
RSM-25209	.500 - .562	.800
RSM-25210	.500 - .625	.800
RSM-25211	.562 - .688	.800
RSM-25212	.625 - .750	.800
RSM-25213	.688 - .812	.800

ITEM NO.	PART NUMBER	DESCRIPTION	MATERIAL	QTY.
1	RSM-25200-B	BODY	ALUMINUM	1
2	SRB-203 THRU SRB-213	BUSHING	NEOPRENE	1
3	SW-200	WASHER	C.R.S. ZINC PLATED	1
4	RSR-200-N	NUT	ALUMINUM	1
5	SOR-1-VNT	O-RING	BUNA-N	1
6	RLM25-BR	LOCK NUT	BRASS, NICKLE PLATED	1

REV.	DATE	CHANGE	UNLESS OTHERWISE SPECIFIED:	NAME	DATE	REMKE REMKE INDUSTRIES 310 CHADDICK DR, WHEELING, IL. 60090	
A	6/14/13	DRAWING RELEASED	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1° BEND ± 1° ONE PLACE DECIMAL ± .015 TWO PLACE DECIMAL ± .010 THREE PLACE DECIMAL ± .005	JCN	6/13	TITLE: RSM-25200 SERIES	
			INTERPRET GEOMETRIC TOLERANCING PER:	CHECKED		SIZE DWG. NO. A RSM-25200 ASSEMBLY	
			MATERIAL ALUMINUM	ENG APPR.		SCALE: 1:1	
			FINISH	MFG APPR.		SHEET 1 OF 1	
			DO NOT SCALE DRAWING	Q.A.			
				PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF REMKE INDUSTRIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF REMKE INDUSTRIES IS PROHIBITED.			