O-RING OPTIONAL ADD: R LOCK NUT OPTIONAL ADD: L M 25 THREAD M 25 THREAD													
													ITEM
NO.	RSM-25200-B		BODY	ALUMINUM	1	_							
2	SRB-211 - SRB-212		BUSHING	NEOPRENE	1	1						RoHS	
3	SOR-1-VNT		O-RING	BUNA-N	1							COMPLIANT	
4	RSR-200-ND		NUT	ALUMINUM	1	-		CATALOG NU		UMBER	SEALING RANGE	BODY BORE	
5	RLM25-BR		LOCK NUT	BRASS, NICKLE PLATED	1			RSM-25211-E		11-E	.562687	.800	
6	R-212-D		MESH	STAINLESS WIRE	1			R	RSM-25212-E		.625750	.800	
REV.	DATE	CHA	NGE		UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL± 1/64				DATE		REMK	E	
A	8/14/13	DRAV	VING RELEASED				DRAWN	JCN	8/13	 310 CH	REMKE INDU	STRIES	
	<u> </u>					AR: MACH±1° BEND ±1° ACE DECIMAL ±.015	CHECKED ENG APPR.				310 CHADDICK DR, WHEELING, IL. 60090 TITLE: RSM-25211-25212-E SERIES		
						LACE DECIMAL ±.010 PLACE DECIMAL ±.005	MFG APPR.			R S			
						RET GEOMETRIC NNCING PER:	Q.A.	RY AND CONFIDENTIAL					
					MATERI FINISH	ALUMINUM	THE INFORMATION DRAWING IS THE REMKE INDUSTRIE	n Containee Sole proper S. Any repro	CONTAINED IN THIS DLE PROPERTY OF ANY REPRODUCTION (HOLE WITHOUT THE		SIZE DWG. NO. RSM-25211-25212-E ASSEMBLY		
					DC	DO NOT SCALE DRAWING IS PROHIBITED.				SCALE:		SHEET 1 OF 1	
		5	ŧ	4	Τ'	3	· I		2	1		1	