	I.25 IUT			1.54	APPROX.	Ο	-RING PTION DD: R	JAL	OPTI ADD	K NUT ONAL : L	SEALING	Ø 1.09 BODY
		RT NUMBER	DESCRIPTION		MATERIAL			]	NU	MBER	RANGE	BORE
NO.	10. FART NUMBER DESCRIPTION				MATERIAL					-20103	.125188	.610
1	RSM-20	100-В	BODY		ALUMINUM		1		RSM-20104		.188250	.610
2	SRB-103	8 - SRB-110	BUSHING		NEOPRENE		1			-20105	.250312	.610
3	SW-100		WASHER	C.	.R.S. ZINC PLATED		1			-20106	.312375	.610
4	RSR-100	)-N	NUT		ALUMINUM 1		1	-		-20107	.375438	.610
5	SOR-38		O-RING		BUNA-N		1	-		-20108	.438500	.610
	6 RLM20-BR			RRA	SS, NICKLE PLATED		1	-		-20109	.500562	.610
			LOCKINOT		UNLESS OTHERWISE SPECIFIED:			NAME				
REV.	DATE CHANGE 6/14/13 DRAWING RE		ELEASED		DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/64 ANGULAR: MACH±1° BEND±1° ONE PLACE DECIMAL ±.010 TWO PLACE DECIMAL ±.010 THREE PLACE DECIMAL ±.005	CHEC	DRAWN CHECKED ENG APPR. MFG APPR.		date	<b>REMKE</b> REMKE INDUSTRIES 310 CHADDICK DR, WHEELING, IL. 6009 TITLE: RSM-20100 SERIES		STRIES ING, IL. 60090
					INTERPRET GEOMETRIC	Q.A.			K2	RSM-20100 SERIES		
				TOLERANCING PER: MATERIAL ALUMINUM FINISH	THE INI DRAW REMKE IN PAR	ROPRIETARY A FORMATION ( ING IS THE SC E INDUSTRIES. RT OR AS A W EN PERMISSIO	Contained Dle propert Any repro 'Hole withc	IN THIS Y OF DUCTION UT THE	SIZE DW	G. NO. RSM-20100 /	ASSEMBLY	