



BRONZE GROUND CLAMP CONNECTOR

• TYPE GPL

Universal parallel or 90° cable connection to rod or pipe



Made from high copper content alloy. Furnished with silicon bronze bolt, nuts and lockwashers.

Part #	Accommodates		Conductor Range	Wire Diameter Range	Approximate Dimensions						
	Rod	IPS			A		B		C		Bolt Dia.
GPL1 *	1/2	1/4	8 Sol.-4 Str.	.128- .232	1 3/8	34	2 1/2	64	1 7/8	47	3/8
GPL2 *	1/2	1/4	4 Sol.-2/0 Str.	.204- .419	1 5/8	41	2 1/2	64	1 7/8	47	3/8
GPL3 *	1/2	1/4	2/0 Sol.-250 MCM	.365- .575	1 7/8	47	2 1/2	64	1 7/8	47	3/8
GPL4	5/8 or 3/4	3/8	8 Sol.-4 Str.	.128- .232	1 3/8	34	2 3/4	70	2	51	3/8
GPL5	5/8 or 3/4	3/8	4 Sol.-2/0 Str.	.204- .419	1 5/8	41	2 3/4	70	2	51	3/8
GPL6	5/8 or 3/4	3/8	2/0 Sol.-250 MCM	.365- .575	1 7/8	47	2 3/4	70	2	51	3/8
GPL7 •	5/8 or 1	3/8 or 3/4	300-500 MCM	.634- .815	2 1/4	57	3 1/2	89	2 3/8	60	1/2
GPL8	7/8 or 1	1/2 or 3/4	8 Sol.-4 Str.	.128- .232	1 3/8	34	2 5/8	67	2 3/8	60	3/8
GPL9	7/8 or 1	1/2 or 3/4	4 Sol.-2/0 Str.	.204- .419	1 5/8	41	2 5/8	67	2 3/8	60	3/8
GPL10	7/8 or 1	1/2 or 3/4	2/0 Sol.-250 MCM	.365- .575	1 7/8	47	3	76	2 3/8	60	3/8
GPL12 •	7/8 or 1	1/2 or 3/4	500-750 MCM	.815- .999	2 5/8	67	3 3/4	95	2 3/4	70	1/2
GPL13 •	7/8 or 1	1/2 or 3/4	750-1000 MCM	.999-1.153	3	76	4	102	3 1/2	89	1/2
GPL14	—	1	8 Sol.-4 Str.	.128- .232	1 3/8	34	2 3/4	70	2 5/8	67	3/8
GPL15	—	1	4 Sol.-2/0 Str.	.204- .419	1 5/8	41	2 3/4	70	2 5/8	67	3/8
GPL16	—	1	2/0 Sol.-250 MCM	.365- .575	1 7/8	47	3 1/4	82	2 5/8	67	3/8
GPL17 •	—	1	300-500 MCM	.634- .815	2 3/8	60	4 1/2	115	3	76	1/2
GPL18 •	—	1	500-750 MCM	.815- .999	2 5/8	67	4 1/2	115	3	76	1/2
GPL19 •	—	1	750-1000 MCM	.999-1.153	3	76	4 3/4	121	3 1/2	89	1/2
GPL20	—	1 1/4	8 Sol.-4 Str.	.128- .232	1 3/8	34	3 1/2	89	3	76	3/8
GPL21	—	1 1/4	4 Sol.-2/0 Str.	.204- .419	1 5/8	41	3 1/2	89	3	76	3/8
GPL22	—	1 1/4	2/0 Sol.-250 MCM	.365- .575	1 7/8	47	3 1/2	89	3	76	3/8
GPL23 •	—	1 1/4	300-500 MCM	.634- .815	2 3/8	60	4 1/4	108	3 3/8	85	1/2
GPL24 •	—	1 1/4	500-750 MCM	.815- .999	2 3/4	70	5	127	3 3/4	95	1/2
GPL25 •	—	1 1/4	750-1000 MCM	.999-1.153	3	76	5 1/2	140	4 1/4	108	1/2
GPL26	—	1 1/2	8 Sol.-4 Str.	.128- .232	1 3/8	34	4	102	3 1/4	82	3/8
GPL27	—	1 1/2	4 Sol.-2/0 Str.	.204- .419	1 5/8	41	4	102	3 1/4	82	3/8
GPL28	—	1 1/2	2/0 Sol.-250 MCM	.365- .575	1 7/8	47	4	102	3 1/4	82	3/8
GPL29 •	—	1 1/2	300-500 MCM	.634- .815	2 3/8	60	4 5/8	118	3 5/8	92	1/2
GPL30 •	—	1 1/2	500-750 MCM	.815- .999	2 3/4	70	5 1/4	133	4	102	1/2
GPL31 •	—	1 1/2	750-1000 MCM	.999-1.153	3	76	5 3/4	146	4 1/2	115	1/2
GPL32	—	2	8 Sol.-4 Str.	.128- .232	1 3/8	34	4 1/4	108	3 3/4	95	3/8
GPL33	—	2	4 Sol.-2/0 Str.	.204- .419	1 5/8	41	4 1/4	108	3 3/4	95	3/8
GPL34	—	2	2/0 Sol.-250 MCM	.365- .575	1 7/8	47	4 1/4	108	3 3/4	95	3/8
GPL35 •	—	2	300-500 MCM	.634- .815	2 3/8	60	5 1/4	133	4	102	1/2
GPL36 •	—	2	500-750 MCM	.815- .999	2 3/4	70	5 1/2	140	4 1/2	115	1/2
GPL37 •	—	2	750-1000 MCM	.999-1.153	3	76	6	152	5	127	1/2

• UL listing is limited to a maximum wire size of 250 MCM.

* Not UL listed for 1/4" Pipe.

Chart continued next page


BRONZE GROUND CLAMP CONNECTOR

• TYPE GPL Continued from preceding page


Part #	Accommodates		Conductor Range	Wire Diameter Range	Approximate Dimensions						Bolt Dia.
	Rod	IPS			A		B		C		
				in	in	mm	in	mm	in	mm	
GPL38	—	2½	8 Sol.-4 Str.	.128- .232	1⅜	34	5	127	4¼	108	⅜
GPL39	—	2½	4 Sol.-2/0 Str.	.204- .419	1⅝	41	5	127	4¼	108	⅜
GPL40	—	2½	2/0 Sol.-250 MCM	.365- .575	1⅞	47	5	127	4¼	108	⅜
GPL41•	—	2½	300-500 MCM	.634- .815	2⅜	60	5⅝	143	4½	115	½
GPL42•	—	2½	500-750 MCM	.815- .999	2¾	70	6	152	5	127	½
GPL43•	—	2½	750-1000 MCM	.999-1.153	3	76	6½	165	5½	140	½
GPL44	—	3	8 Sol.-4 Str.	.128- .232	1⅜	34	5½	140	4¾	121	⅜
GPL45	—	3	4 Sol.-2/0 Str.	.204- .419	1⅝	41	5½	140	4¾	121	⅜
GPL46	—	3	2/0 Sol.-250 MCM	.365- .575	1⅞	47	5½	140	4¾	121	⅜
GPL47•	—	3	300-500 MCM	.634- .815	2⅜	60	6¼	158	5¼	133	½
GPL48•	—	3	500-750 MCM	.815- .999	2¾	70	6¾	171	5½	140	½
GPL49•	—	3	750-1000 MCM	.999-1.153	3	76	7¼	184	6	152	½
GPL50	—	3½	8 Sol.-4 Str.	.128- .232	1⅜	34	6¼	158	5¼	133	⅜
GPL51	—	3½	4 Sol.-2/0 Str.	.204- .419	1⅝	41	6¼	158	5¼	133	⅜
GPL52	—	3½	2/0 Sol.-250 MCM	.365- .575	1⅞	47	6¼	158	5¼	133	⅜
GPL53•	—	3½	300-500 MCM	.634- .815	2⅜	60	6¾	171	5¾	146	½
GPL54•	—	3½	500-750 MCM	.815- .999	2¾	70	7½	191	6	152	½
GPL55•	—	3½	750-1000 MCM	.999-1.153	3	76	8	203	6½	165	½
GPL56	—	4	8 Sol.-4 Str.	.128- .232	1⅜	34	6⅜	161	5¾	146	⅜
GPL57	—	4	4 Sol.-2/0 Str.	.204- .419	1⅝	41	6⅜	161	5¾	146	⅜
GPL58	—	4	2/0 Sol.-250 MCM	.365- .575	1⅞	47	6⅜	161	5¾	146	⅜
GPL59•	—	4	300-500 MCM	.634- .815	2⅜	60	6¾	171	6¼	158	½
GPL60•	—	4	500-750 MCM	.815- .999	2¾	70	8	203	6½	165	½
GPL61•	—	4	750-1000 MCM	.999-1.153	3	76	8½	216	7	178	½
GPL68	—	5	8 Sol.-4 Str.	.128- .232	1⅜	34	6⅜	161	6¾	171	⅜
GPL69	—	5	4 Sol.-2/0 Str.	.204- .419	1⅞ ₃₂	38	5⅝	143	6⅓ ₁₆	173	⅜
GPL70	—	5	2/0 Sol.-250 MCM	.365- .575	1⅞	47	6⅞	155	6⅓ ₁₆	173	⅜
GPL71•	—	5	300-500 MCM	.634- .815	2⅝ ₁₆	59	6⅞	155	7⅞	181	½
GPL75	—	6	4 Sol.-2/0 Str.	.204- .419	1⅞ ₃₂	38	5⅞	149	7⅞	200	⅜
GPL76	—	6	2/0 Sol.-250 MCM	.365- .575	1⅞	47	7⅞	181	7⅓ ₁₆	199	⅜
GPL77•	—	6	300-500 MCM	.634- .815	2⅝ ₁₆	59	6⅓ ₁₆	157	8⅓ ₁₆	208	½
GPL87	—	8	4 Sol. 2/0 Str.	.204- .419	1⅞ ₃₂	38	7⅞	181	9⅞	251	⅜

• UL listing is limited to a maximum wire size of 250 MCM by UL467.

K-SPEC® ECONOMY GROUND PIPE CLAMPS



KP1



KP1DB

- Manufactured from cast copper alloy
- Supplied with steel screws, plated for corrosion resistance*
- Provides maximum conductivity & strength
- Suitable for direct burial, supplied with silicon bronze hardware†
- Used to connect copper grounding conductor to water pipe, ground rods & copper water tubing



Part No	Rod Size	Wire Range	
		Min	Max
KP1*	1/2 – 1	10 SOL	2 STR
KP1DB†	1/2 – 1	10 SOL	2 STR
KP2DB†	1 1/4 – 2	10 SOL	2 STR