

BRASS DOME-TOP STRAIN RELIEF CONNECTORS & LOCK NUTS "METRIC"

Specifications

Technical Details:

- Material:** Brass, Nickel Plated
- Sealing Ring:** Neoprene
- Protection Class:** IP68
- Temp. Range:** -40°C to +100°C
- Clamping Insert:** Polyamide 6
- O Ring:** NBR (Buna N, Nitrile)




Part #	Cable Range	Thread Type Size	DIMENSIONS (INCHES)			Locking Nuts (Nickel Plated Brass)	
			Clearance Hole +.10/.010	Thread Length Fitting	Wrenching Flats	PART #	THREAD TYPE & SIZE
Dome Fitting	(Inches)					Locking Nut	
BRM12AA BRM12AR	.12 - .26 .08 - .20	M12	.49	.24	.55	NM-12-BR	M12
BRM16AA BRM16AR	.16 - .31 .07 - .24	M16	.63	.28	.67	NM-16-BR	M16
BRM20AA BRM20AR	.24 - .47 .11 - .28	M20	.79	.32	.87	NM-20-BR	M20
BRM25AA BRM25AR	.39 - .55 .27 - .47	M25	.98	.32	.95	NM-25-BR	M25
BRM32AA BRM32AR	.51 - .71 .35 - .63	M32	1.26	.35	1.18	NM-32-BR	M32
BRM40AA BRM40AR	.71 - .98 .51 - .79	M40	1.58	.35	1.58	NM-40-BR	M40
BRM50AA BRM50AR	.87 - 1.26 .79 - 1.02	M50	1.97	.35	1.97	NM-50-BR	M50

G



DOME CAP STANDARD EMC CABLE GLANDS WITH ISO/METRIC OR NPT THREADS



SPECIFICATIONS

- Materials:** Brass, Nickel-Plated
- Sealing Ring:** Neoprene
- Protection Class:** IP68
- Clamping Insert:** Polyamide 6
- O Ring:** NBR (Buna N, Nitrile)



Dome Cable Glands	Locking Nuts	Cable Range (in.)	Type & Size	Clearance Hole (in.) (A)	Thread Length (in.) (B)	Across Flats (in.) (C)
ISO/METRIC THREADS						
BRME16	NM-16-BR	.16 - .31	M16 x 1.5	0.63	0.28	0.71
BRME20	NM-20-BR	.24 - .47	M20 x 1.5	0.79	0.31	0.87
BRME25	NM-25-BR	.39 - .55	M25 x 1.5	0.98	0.31	1.06
NPT THREADS						
BRNE13	LN-50	.24 - .47	1/2" NPT	0.83	0.51	0.87
BRNE21	LN-75	.51 - .71	3/4" NPT	1.14	0.51	1.18