

JUNIOR PULLING GRIPS

Junior Pulling Grips are reusable tools designed for pulling cables, wire and rope. Constructed of galvanized steel mesh, these grips are designed for use in pulling single cable or bundled

cables in overhead, underground, electrical construction and industrial applications. Customized sizes and designs available.



| Cable Range | Part # | Description | Approx.* Breaking Strength | Length | |
|-------------|-----------------|--|----------------------------|--------|------|
| | | | | Eye | Mesh |
| .25- .36 | 3305-002 | JP-25 | 450 | 3¼ | 4¼ |
| .37- .49 | 3305-003 | JP-37 | 900 | 3¼ | 7 |
| .50- .61 | 3305-004 | JP-50 | 1300 | 4¼ | 8½ |
| .62- .74 | 3305-005 | JP-62 | 1950 | 5 | 10 |
| .75- .99 | 3305-006 | JP-75 | 2800 | 5¼ | 10 |
| 1.00-1.25 | 3305-007 | JP-100 | 3900 | 6½ | 11½ |
| .25-1.25 | 3305-008 | JPK-1 Kit includes: JP-25, JP-37, JP-50, JP-62 JP-75, JP-100 | — | — | — |

LIGHT DUTY PULLING GRIPS

Light Duty Pulling Grips are single weave construction made of a high grade galvanized steel strand. They feature a flexible eye for easy attachment to a pulling line.

Application

Light duty Pulling Grips are used in general underground electrical construction where pulling tensions are low. They are also used for wiring industrial plants and commercial buildings.



| Cable Range | Part # | Description | Approx.* Breaking Strength | Length | |
|-----------------|-----------------|-------------|----------------------------|--------|------|
| | | | | Eye | Mesh |
| Short | | | | | |
| .50- .61 | 3303-001 | LD-050S | 2800 | 5 | 11 |
| .62- .74 | 3303-002 | LD-062S | 2800 | 5 | 11 |
| .75- .99 | 3303-003 | LD-075S | 4000 | 6 | 12 |
| 1.00-1.24 | 3303-004 | LD-100S | 5300 | 7 | 13 |
| 1.25-1.49 | 3303-005 | LD-125S | 5300 | 7 | 14 |
| 1.50-1.74 | 3303-006 | LD-150S | 6800 | 8 | 15 |
| 1.75-1.99 | 3303-007 | LD-175S | 8500 | 8 | 17 |
| 2.00-2.49 | 3303-008 | LD-200S | 8500 | 9 | 18 |
| 2.50-2.99 | 3303-009 | LD-250S | 10600 | 9 | 18 |
| 3.00-3.49 | 3303-010 | LD-300S | 14700 | 10 | 20 |
| Standard | | | | | |
| .50- .61 | 3303-011 | LD-050 | 2800 | 5 | 16 |
| .62- .74 | 3303-012 | LD-062 | 2800 | 5 | 16 |
| .75- .99 | 3303-013 | LD-075 | 4000 | 6 | 20 |
| 1.00-1.24 | 3303-014 | LD-100 | 6800 | 7 | 20 |
| 1.25-1.49 | 3303-015 | LD-125 | 6800 | 7 | 21 |
| 1.50-1.99 | 3303-016 | LD-150 | 6800 | 8 | 23 |
| 2.00-2.49 | 3303-017 | LD-200 | 8500 | 9 | 25 |
| 2.50-2.99 | 3303-018 | LD-250 | 8500 | 9 | 27 |
| 3.00-3.49 | 3303-019 | LD-300 | 10600 | 10 | 30 |
| 3.50-3.99 | 3303-020 | LD-350 | 14700 | 10 | 32 |

