

## Service Lights

### Fluorescent Service Lights (Standard)

- 13 Watt Fluorescent Bulbs
- Shatter resistant housing
- Polycarbonate lens provides a 270° arc of light

- \*769703** 15ft (4.57m) 18/2 cord. 360° swivel hook **\*NEW**
- \*769704** 25ft (7.62m) 16/3 cord. 360° swivel hook **plus** magnetic mounting clip. 3-prong receptacle on handle **\*NEW**

### Fluorescent Service Lights (Retractable Reel)

- 13 Watt (Energy Saving) Fluorescent Bulbs
- Shatter resistant housing & reels
- Polycarbonate lens provides a 270° arc of light

- \*769700** 20ft (6.10m) 18/2 cord. 360° swivel hook. Ceiling or wall mount retractable reel. **\*NEW**
- \*769705** 30ft (9.14m) 16/3 cord. 360° swivel hook. 3-prong receptacle on handle. Ceiling or wall mount steel retractable reel. **\*NEW**

### Incandescent Service Lights – Medium Duty

**769707** 25ft (7.62m) 18/3 cord is oil & flame retardant. Withstands temperatures between 41°C to 29°C (105°F to -20°F). Two 3-prong receptacles on handle. Galvanized metal safety guard

**769708** Same characteristics as **769707** except with a 50' (15.24m) cord

### Incandescent Service Lights – Heavy Duty

**769709** 25ft (7.62m) 16/3 SJEOW cord for extra flexibility. Withstands temperatures between 105°C to -34°C (221°F to -29°F). Metal safety guard. Two 3-prong receptacles on handle. 360° swivel hook for extra convenience.

**769717** 25ft (7.62m) 16/3 SJWT cord. Withstands temperatures between 60°C to -34°C (140°F to -29°F). Impact resistant polycarbonate handle has a 3-prong receptacle. Multi-directional On-Off switch can be operated from any angle. Hinged plated steel safety guard.

**769770** 25ft (7.62m) 16/3 SJOW cord for extra flexibility. Withstands temperatures between 90°C to -34°C (194°F to -29°F). Impact resistant polycarbonate handle has a 3-prong receptacle. Multi-directional On-Off switch can be operated from any angle. Oil & flame retardant jacket. Hinged plated steel safety guard.

**769771** Same characteristics as **769770** except with a 50' (15.24m) cord

**769729** Same characteristics as **769770** except on a steel retractable cord reel. Safety switch on the reel shuts off current at the power source.

### Replacement Parts for Heavy Duty Incandescent Service Lights

(for **769770**, **769771**, **769717**, **769729** only)

- 769734** 3 conductor handle and guard with multi-directional switch and power tool receptacle
- 769735** 110 volt, 60 watt rough service bulb, 2 per package
- 769761** Multi-directional socket switch
- 769975** Hinged plated steel safety guard assembly

