

EUREKA-HD SERIES

NORTH AMERICAN - 30A

EUREKA[PIN&SLEEVE] Series



SPLASHPROOF - IP44

Poles & Wires	Configuration			Voltage/ Colour Coding	Plug (Male)	Connector (Female)	Receptacle (Female)	Inlet (Male)	Cable O.D. Range Inches
	Receptacle/ Connector	Plug/Inlet	Clock position						
2P 3W			4h	125	SCM330P4S	SCM330C4S	SCM330R4S	SCM330B4S	.675-.91
2P 3W			6h	250	SCM330P6S	SCM330C6S	SCM330R6S	SCM330B6S	.675-.91
2P 3W			5h	277	SCM330P5S	SCM330C5S	SCM330R5S	SCM330B5S	.675-.91
2P 3W			7h	480	SCM330P7S	SCM330C7S	SCM330R7S	SCM330B7S	.675-.91
3P 4W			12h	125/250	SCM430P12S	SCM430C12S	SCM430R12S	SCM430B12S	.675-.91
3P 4W			9h	3ø250	SCM430P9S	SCM430C9S	SCM430R9S	SCM430B9S	.675-.91
3P 4W			6h	380-415	SCM430P6S	SCM430C6S	SCM430R6S	SCM430B6S	.675-.91
3P 4W			7h	3ø480	SCM430P7S	SCM430C7S	SCM430R7S	SCM430B7S	.675-.91
3P 4W			5h	3ø600	SCM430P5S	SCM430C5S	SCM430R5S	SCM430B5S	.675-.91
4P 5W			9h	3øY120-208	SCM530P9S	SCM530C9S	SCM530R9S	SCM530B9S	.675-.91
4P 5W			6h	220/380 240/415	SCM530P6S	SCM530C6S	SCM530R6S	SCM530B6S	.675-.91
4P 5W			7h	3øY277/480	SCM530P7S	SCM530C7S	SCM530R7S	SCM530B7S	.675-.91
4P 5W			5h	3øY347/600	SCM530P5S	SCM530C5S	SCM530R5S	SCM530B5S	.675-.91

REFERENCE STANDARDS

IEC 60309-1

Plugs, socket-outlets and couplers for industrial purposes.
Part 1: general requirements.

IEC 60309-2

Plugs, socket-outlets and couplers for industrial purposes.
Part 2: dimensional interchangeability requirements for pin
and contact-tube accessories.

UL 1682

Plugs, receptacles and cable
connectors of the pin and sleeve type.

UL 1686

Standard for pin and sleeve configuration.

QUALITY MARKS



UL LISTED:
E238171, E238172



UL CLASSIFIED:
E238170



DIMENSIONS




PLUG IP44

	A		B		C		Corp Grip Range	
	inches	mm	inches	mm	inches	mm	inches	mm
16/20A 2P3W	2.26	58	6.20	157	4.76	121	.570-.710	14-18
16/20A 3P4W	2.52	64	6.47	164	5.04	128	.570-.710	14-18
16/20A 4P5W	2.85	73	7.02	178	5.58	142	.570-.710	14-18
30/32A 2P3W	2.85	73	7.37	187	5.58	142	.675-.910	17-23
30/32A 3P4W	2.85	73	7.37	187	5.58	142	.675-.910	17-23
30/32A 4P5W	3.13	80	8.15	207	6.36	162	.675-.910	17-23

CONNECTOR IP44

	A		B		C		Corp Grip Range	
	inches	mm	inches	mm	inches	mm	inches	mm
16/20A 2P3W	2.18	55	6.53	166	3.07	73	.570-.710	14-18
16/20A 3P4W	2.43	62	6.83	173	3.33	80	.570-.710	14-18
16/20A 4P5W	2.81	71	7.41	188	3.79	91	.570-.710	14-18
30/32A 2P3W	2.81	71	7.81	198	3.79	91	.675-.910	17-23
30/32A 3P4W	2.81	71	7.81	188	3.79	91	.675-.910	17-23
30/32A 4P5W	3.09	79	8.62	219	4.17	101	.675-.910	17-23



INLET IP44

	A		B		C		D		E		F		G		H	
	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm
16/20A 2P3W	2.26	58	1.96	50	4.50	114	.75	19	3.87	98	3.87	98	2.38	60	.282	7.2
16/20A 3P4W	2.52	64	1.96	50	4.50	114	.75	19	3.87	98	3.87	98	2.38	60	.282	7.2
16/20A 4P5W	2.85	73	1.96	50	4.50	114	.75	19	3.87	98	3.87	98	2.38	60	.282	7.2
30/32A 2P3W	2.85	73	2.32	59	4.50	114	1.32	34	3.87	98	3.87	98	2.38	60	.282	7.2
30/32A 3P4W	2.85	73	2.32	59	4.50	114	1.32	34	3.87	98	3.87	98	2.38	60	.282	7.2
30/32A 4P5W	3.13	80	2.32	59	4.50	114	1.32	34	3.87	98	3.87	98	2.38	60	.282	7.2

RECEPTACLE IP44

	A		B		C		D		E		F		G		H		I	
	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm
16/20A 2P3W	2.18	55	2.11	54	2.97	76	0.94	24	2.36	60	2.36	60	2.38	60	.219	5.5	3.07	73
16/20A 3P4W	2.43	62	2.13	54	2.97	76	0.94	24	2.36	60	2.36	60	2.38	60	.219	5.5	3.33	80
16/20A 4P5W	2.81	71	2.17	55	2.97	76	0.94	24	2.36	60	2.36	60	2.38	60	.219	5.5	3.79	91
30/32A 2P3W	2.81	71	2.56	65	2.97	76	1.52	39	2.36	60	2.36	60	2.38	60	.219	5.5	3.79	91
30/32A 3P4W	2.81	71	2.56	65	2.97	76	1.52	39	2.36	60	2.36	60	2.38	60	.219	5.5	3.79	91
30/32A 4P5W	3.09	79	2.60	66	2.97	76	1.52	39	2.36	60	2.36	60	2.38	60	.219	5.5	4.17	101

(Dimensions in mm)

EUREKA-HD SERIES

■ BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistance	Resistant	Limited Resistance	Resistant	Not Resistant	Not Resistant	Not Resistant	Limited Resistance	Resistant	Resistant

■ WIRING AND INSTALLATION

Cross-section of connectable conductors (awg/mm²)

Rated current		Plugs, connectors and appliance inlets				Receptacle			
Series I	Series II	Min awg	mm²	Max awg	mm²	Min awg	mm²	Max awg	mm²
16A	20A	16	1	12	2.5	16	1.5	12	4
32A	30A	14	2.5	10	6	14	2.5	8	10
63A	60A	10	6	6	16	10	6	4	25
125A	100A	6	16	2	50	4	25	0	70

Cord grip range

(Plugs and connectors)

Rated current		Outside Ø mm			
Series I	Series II	Min Inches	mm²	Max Inches	mm²
16A	20A	.570	14	.710	18
32A	30A	.675	17	.910	23
63A	60A	.937	24	1.375	35
125A	100A	1.02	26	1.790	45

■ TECHNICAL CHARACTERISTICS FOR BACK BOX

Protection degree (IEC 60529):	IP66/IP67
Operating ambient temperature:	-25°C +40°C
Max. operating ambient temperature:	+70°C
Self-extinguishing (IEC 60695-2-I):	GW test 850°C
Self-extinguishing (UL94):	5VA (3mm)
Material:	PC siloxane
IK degree at 20°C (EN 50102):	IK10 (20J)

■ TECHNICAL CHARACTERISTICS FOR PIN & SLEEVE

Rated current:	16A - 32A - 63A - 125A (SERIES I) 20A - 30A - 60A - 100A (SERIES II)
Rated voltage:	100÷690V~
Frequency:	D.C. - 50÷500Hz
Insulating voltage:	500/690V~
Protection degree (IEC 60529):	IP44 - IP67
Operating ambient temperature according to the reference standard:	-25°C + 40°C
Max. operating ambient temperature:	+70°C
Self-extinguishing (IEC 60695-2-I):	GW test 650°C / 850°C
Self-extinguishing (UL94):	V1 (3mm)
Material:	VALOX®
IK degree at 20°C (EN 50102):	IK10 (20J)

■ PERFORMANCE - ELECTRICAL (SERIES I)

Dielectric Voltage withstand:	3000 Volts for 1 minute per IEC 60309-1, Clause 19
Maximum Working Voltage:	690VAC/250 VDC (minimum creepage and clearances per IEC)
Current Interrupting/ Load Breaking:	Tested to 125% rated current at 110% rated voltage per IEC309-1 clause 20
Temperature Rise:	Maximum 50°C rise at rated current per IEC309-1 Clause 22, Table 8
Endurance with Load:	16 Amp: 5000 cycles; Load only
Per IEC 60309-1 Clause 21:	32 Amp: 1000 cycles - Alternating load 63 Amp: 1000 cycles - Alternating load 125 Amp: 250 cycles - Alternating load

■ PERFORMANCE - ELECTRICAL (SERIES II)

Dielectric Voltage Withstand:	3000 Volts for 1 minute (fixed devices) 2200 Volts for 1 minute (portable devices)
Maximum Working Voltage:	600VAC/250 VDC (minimum creepage and clearances per UL 840)
Current Interrupting/ Load Breaking:	Tested to 150% of full rated current for circuit interrupting
Temperature Rise:	Maximum 30°C rise at full rated current after 50 cycles overload at 150% rated load at 0.75-pf
Horsepower Ratings:	Per Nec 430-151b reference for non-interrupting ratings
Endurance with Load:	20 Amp: 5000 cycles; Load only
Per IEC 60309-1 Clause 21:	30 Amp: 1000 cycles - Alternating load 60 Amp: 1000 cycles - Alternating load 100 Amp: 250 cycles - Alternating load

■ MATERIALS FOR PIN & SLEEVE (SERIES I & II)

Housing:	Valox®
Contact Carriers:	Valox®
Cable Gland Nut:	Valox®
Cable Bushing:	Solid neoprene, onion ring type
O-Ring, Seals & Gaskets:	Solid neoprene
Pins & Sleeves:	Nickel plated brass
Sleeve Force Ring:	Zinc plated steel
Terminal Screws:	Nickel plated steel
Flap/Screw Cover Springs:	Stainless steel
SNAP-ON Spring:	Stainless steel
Mounting Flanges:	Valox®

■ PERFORMANCE - MECHANICAL (SERIES I)

Cold (-25°C) Impact Resistance:	Per IEC 60309-1 Clause 24; (-25°C) with 75cm drop
Cable O.D. Accommodation:	Round portable service cords from 14.5mm O.D. through 50mm O.D.
Terminal Identification:	In accordance with IEC 60309-1 standards; as L1-L2-L3-N-G
Cable Pull-Out Force:	In accordance with IEC 60309-1, Clause 23

■ PERFORMANCE - MECHANICAL (SERIES II)

Cold (-25°C) Impact Resistance:	Per UL 1682 Section 34 and IEC 60309-1 Clause 24
Cable O.D. Accommodation:	Round portable service cord from 0.57" O.D. through 1.79" O.D.
Terminal Identification:	In accordance with UL 1682 standards and IEC 60390-1: as L1-L2-L3-N-G
Cable Pull-Out Force:	Per UL 1682 Section 33 and IEC 60309-1 Clause 23

■ PERFORMANCE - ENVIRONMENTAL (SERIES I & II)

Corrosion Resistance:	All metallic components stainless steel or nickel plated brass Sleeve pressure rings of zinc plated steel
-----------------------	--

■ MATERIALS FOR BACK BOX (SERIES I & II)

Housing:	PC siloxane
Gasket:	Solid neoprene
Screws:	Stainless steel
Grounding plate:	zinc-coated steel

Standard Interface / World Ready

Full International Compliances

EN 60309

UL Classification to IEC 60309-1 and IEC 60309-2.

cULus Listing: UL 1682/1686 and CSA C22.2

No. 182.1.

CE conforms to EC Low Voltage Directive.

North American and Global Voltage

Polarization "clock positions" available in all standard ratings.

Solid, Safe Voltage Selections

One-Piece contact carriers with Full-Color IEC standard voltage-phasing Coding ensures correct product application every time.

EUREKA-HD SERIES




Industrial Pin & Sleeve for North American Configurations (Series II)

COLOUR CODE CLOCK POSITION

The operating voltage is identified by conventional colours as shown in the table:

RATED VOLTAGE	COLOUR
110-130V	Yellow
208-250V	Blue
380-480V	Red
500-690V	Black
277V	Grey
125/250V	Orange


CONNECTOR AND RECEPTACLE (FRONT VIEW)




(*) Major keyway

CLOCK FACE POSITION

North American ratings viewing connector and receptacle from the front, clock hour position (h) is established by the position of the earth contact respect the major keyway which is always situated at 6h clock position.



CATALOGUE NUMBERING SYSTEM



■ WATERTIGHT – IP67



IP67

Watertight design and construction meet stringent IP67 internal protection standards.

Rugged thermoplastic housings resist impact or abuse and provide excellent corrosion resistance.

Unique Scame strain relief grip and sealing system assure superior cable retention and watertight conductor termination.

Ideal for outdoor, wet marine and washdown applications.

Unique 75% faster assembly with Snap-on handle locking, and cable grip system.

■ SPLASHPROOF – IP44



IP44

Suitable for indoor use where splashing liquids and other contaminants may interfere with electrical connections.

Ideal for most heavy commercial applications and light industrial applications.

Available 16A, 20A, 30A and 32A Amp ratings.




No Tools, No Screws Necessary

Snap-on locking handle saves 75% on assembly time.

Unique Snap-on assembly feature on 16A, 20A, 30A and 32A Amp plugs and connectors makes installation and inspection fast and reliable.

Captive gaskets in handles seal out water, chemicals and dust.



Easy Action Single-Wiring Point Access Saves Time Wiring

All terminal screws face in same direction allowing installer to make safe and secure conductor terminations in 30% less time than other devices. Rugged, corrosion free thermoplastic housings are colour-coded for safe reliable connections to all other mating type /polarizations, with raised earth terminal standard.



Simple Cable Clamping

Threaded cable gland on 16/32A and 20/30A devices makes assembly fast and easy.

One-piece lock screw verifies clamp locking hold, with no external metal contact possible (16/32A and 20/30A devices).



Unique and Quick

One-piece cable gland with locking screw loads to cable followed by cable grip 6-Finger cable clamp/grip piece.

Watertight onion ring bushing fits a wide variety of outside diameters.



Watertight and cable Grip Safety

Grip cable flexible 6-Finger clamp teeth holds well beyond all agency test pullout forces.

No internal clamps required.

Available in all amperages.



The Performance Connection

Watertight spring-loaded covers with high-strength flex-hinge screw covers on IP67 devices.

Flap covers on IP44 splashproof styles.

Safety, performance and durability for all EN 60309 applications worldwide.

EUREKA-HD SERIES

■ WATERTIGHT – IP67

Safe Connections Standard

- Earth contacts make first, break last for safe connections even under load

