

Primary Wire



Type SXL

Type TEW

Speaker Wire

TYPE SXL to SAE Specification J1128-125°C (257°F) Temperature Rating

General purpose, low tension cable, crosslinked polyethylene insulated jacket provides toughness combined with outstanding heat resistance. Resists grease, oil, gasoline and chemicals. Clean stripping for easy use. Ideally suited for heavy-duty applications. For applications of up to 50 volts.

100' Spools (30.5 m)

Gauge	Outside Diameter	Stranding	Black	Blue	Brown	Green	Orange	Purple	Red	White	Yellow
16	.129"	19 x .0133"	768840	768841	768842	768843	768847		768844	768845	768846
14	.151"	19 x .0142"	768850	768851	768852	768853	768857	*768858	768854	768855	768856
12	.172"	19 x .0179"	768860	768861	768862	768863	768867	*768868	768864	768865	768866
10	.203"	19 x .0234"	768770			768773			768774	768775	768776
8	.226"	7 x 12 x .0142"	768780						768784	768785	

SXL wire on 1000 ft spools available upon request.

***NEW**

TYPE TEW Stranded Copper Conductor, (PVC Insulation 600 VOLTS) -40°C (-40°F) to 105°C (221°F) Temperature Rating



For use in internal wiring of electrical and electronic equipment. Applications include electric ranges, heating equipment, lighting fixtures, panels and meters. CSA & UL Approved

Non-Tinned TEW

98.4' Spools (30 m)

Gauge	Outside Diameter	Stranding	Black	Blue	Brown	Green	Orange	Red	White	Yellow	Purple	Grey
18	.109"	16 x .010"	768600	768601	768602	768603	768604	768605	768606	768607	768599	768608
16	.122"	26 x .010"	768609	768610	768611	768612	768613	768614	768615	768616	768598	768617
14	.136"	41 x .010"	768618	768619	768620	768621	768622	768623	768624	768625	768597	768626
12	.159"	65 x .010"	768627	768628	768629	768630	768631	768632	768633	768634		
10	.183"	104 x .010"	*768636					*768641	*768642			

Available in 984 ft (300 m) upon request.

***NEW**

Tinned TEW (for Marine Applications)

98.4' Spools (30 m)

Gauge	Outside Diameter	Stranding	Black	Blue	Brown	Green	Orange	Red	White	Yellow	Purple	Grey
18	.109"	16 x .010"	768654	768655	768656	768657	768658	768659	768660	768661	768662	768663
16	.122"	26 x .010"	768664	768665	768666	768667	768668	768669	768670	768671	768672	768673
14	.136"	41 x .010"	768674	768675	768676	768677	768678	768679	768680	768681	768682	768683
12	.159"	65 x .010"	768684	768685	768686	768687	768688	768689	768690	768691	768692	768693
10	.183"	104 x .010"	*768694	*768695	*768696	*768697	*768698	*768699	*768700	*768701	*768702	*768703

***NEW**

Speaker Wire

22 gauge-2 conductor speaker wire. Bonded parallel clear vinyl jacketed conductors. Wire is polarized using bare copper stranding on one side and tin plated copper stranding on the other side.

768403 100' (30.5) spool.

Tinned for Marine Applications!