



# HOLDER FOR CYLINDRICAL FUSES

32 A / 690 V, 10 X 38

For conventional cabling, elecDirect.com offers a comprehensive range of panel components suitable for either plate or DIN-rail mounting. Fuses and the associated connection technology meet the highest safety and quality requirements set by international standards.

	31110	31112	31113
<b>Description</b>	Art. No.: 31110 Ambus EasySwitch holder for cylindrical fuses 10 x 38 1-pole	Art. No.: 31112 Ambus EasySwitch holder for cylindrical fuses 10 x 38 2-pole	Art. No.: 31113 Ambus EasySwitch holder for cylindrical fuses 10 x 38 3-pole
<b>Standards</b>	IEC / EN 60947-3 IEC / EN 60269-2-1(III) UL 512 CSA C22.2 No. 39	IEC / EN 60947-3 IEC / EN 60269-2-1(III) UL 512 CSA C22.2 No. 39	IEC / EN 60947-3 IEC / EN 60269-2-1(III) UL 512 CSA C22.2 No. 39
<b>Approvals</b>	IEC (CB), GOST, CCC, CSA, UL Type No.: AES10x38 	IEC (CB), GOST, CCC, CSA, UL Type No.: AES10x38 	IEC (CB), GOST, CCC, CSA, UL Type No.: AES10x38 
<b>Electrical Data</b>	<b>IEC, EN:</b> 32 A, 690 V (50-60 Hz) <b>UL, CSA:</b> 30 A, 600 V (60 Hz) <b>Rated insulation voltage:</b> 800 V utilisation category to IEC 60947-3 AC-22B (400 V) Conditional rated short circuit current 50 kA with fuse links gG  <b>For fuse links to IEC 60269-2-1(III) with rated power dissipation:</b> max. 3 W gG/gL max. 1,2 W aM <b>Power dissipation at nominal current:</b> 0,3 Watt	<b>IEC, EN:</b> 32 A, 690 V (50-60 Hz) <b>UL, CSA:</b> 30 A, 600 V (60 Hz) <b>Rated insulation voltage:</b> 800 V utilisation category to IEC 60947-3 AC-22B (400 V) Conditional rated short circuit current 50 kA with fuse links gG  <b>For fuse links to IEC 60269-2-1(III) with rated power dissipation:</b> max. 3 W gG/gL max. 1,2 W aM <b>Power dissipation at nominal current:</b> 0,6 Watt	<b>IEC, EN:</b> 32 A, 690 V (50-60 Hz) <b>UL, CSA:</b> 30 A, 600 V (60 Hz) <b>Rated insulation voltage:</b> 800 V utilisation category to IEC 60947-3 AC-22B (690 V) Conditional rated short circuit current with fuse links gG 100 kA (500 V) 80 kA (690 V) <b>For fuse links to IEC 60269-2-1(III) with rated power dissipation:</b> max. 3 W gG/gL max. 1,2 W aM <b>Power dissipation at nominal current:</b> 0,9 Watt
<b>Mechanical Data</b>	<b>Width x Height x Depth (mm):</b> 18 x 81 x 58 <b>Weight (kg/100):</b> 6,3  <b>Fastening method:</b> clip-on mounting	<b>Width x Height x Depth (mm):</b> 36 x 81 x 58 <b>Weight (kg/100):</b> 12,8  <b>Fastening method:</b> clip-on mounting	<b>Width x Height x Depth (mm):</b> 54 x 81 x 58 <b>Weight (kg/100):</b> 19,3  <b>Fastening method:</b> clip-on mounting
<b>Pack Size</b>	12	6	4