


K-SPEC® COPPER ONE HOLE SHORT BARREL LUGS

One-Hole Lug Short Barrel



- Short barrel designed for regular duty application
- Colour coded to show proper die number and colour
- U.L. listed per 486A upto 35kv
- Ideal for confined areas
- Inspection window to visually assure full cable insertion

Part No.	WIRE RANGE	STUD HOLE SIZE IN "IN"	COLOUR CODE	DIMENSION IN INCHES					
				A	A1	B	C	E	F
SBL8S14 SBL8S15	8 Str.	#10 1/4	RED	1.20	0.44	0.42	0.08	0.28	0.59
SBL6S SBL6S1 SBL6S2	6 Str.	#10 1/4 5/16	BLUE	1.50	0.71	0.42 0.48	0.08 0.07	0.30	0.67
SBL4S SBL4S1 SBL4S10 SBL4S2	4 Str.	#10 1/4 5/16 3/8	GREY	1.50 1.50	0.71 0.71	0.49 0.56	0.09 0.08	0.31 0.31	0.67 0.67
SBL2S SBL2S1 SBL2S2	2 Str.	1/4 5/16 3/8	BROWN	1.80	0.83	0.60	- 0.10	0.37	0.81
SBL1S9 SBL1S SBL1S1	1 Str.	1/4 5/16 3/8	GREEN	1.83	0.83	0.67	0.11	0.37	0.81
SBL1/0S19 SBL1/0S SBL1/0S1	1/0 Str.	1/4 5/16 3/8	PINK	1.83	0.83	0.74	0.13	0.37	0.81
SBL2/0S20 SBL2/0S21 SBL2/0S SBL2/0S4	2/0 Str.	1/4 5/16 3/8 1/2	BLACK	2.24	0.94	0.81	0.12	0.47	1.06
SBL3/0S14 SBL3/0S15 SBL3/0S SBL3/0S1	3/0 Str.	1/4 5/16 3/8 1/2	ORANGE	2.36	0.98	0.90	0.13	0.47	1.06
SBL4/0S19 SBL4/0S25 SBL4/0S SBL4/0S1	4/0 Str.	1/4 5/16 3/8 1/2	PURPLE	2.36	0.98	1.00	0.13	0.47	1.06
SBL025S2 SBL025S	250 MCM	3/8 1/2	YELLOW	2.48	1.06	1.09	0.15	0.47	1.06
SBL030S SBL030S8	300 MCM	1/2 5/8	WHITE	2.49 2.80	1.06 1.06	1.19 1.19	0.15 0.15	0.52 0.52	1.06 1.38
SBL035S SBL035S3	350 MCM	1/2 5/8	RED	2.61 2.64	1.10 1.10	1.28 1.28	0.17 0.17	0.52 0.52	1.06 1.38
SBL040S4 SBL040S	400 MCM	1/2 5/8	BLUE	2.95	1.18	1.39	0.18	0.52	1.38
SBL050S2 SBL050S	500 MCM	1/2 5/8	BROWN	3.28	1.38	1.54	0.22	0.52	1.38
SBL060S	600 MCM	5/8	GREEN	3.50	1.50	1.72	0.25	0.69	1.46
SBL075S	750 MCM	5/8	BLACK	4.37	1.85	1.90	0.27	0.69	1.85

Approved with Burndy, Thomas and Betts, ILSCO and Huskie Tooling.