


K-SPEC® COPPER ONE HOLE LONG BARREL LUGS

One-Hole Lug Long Barrel



- Colour coded to show proper die number and colour
- U.L. listed per 486A upto 35kv
- Ideal for industrial oil, rig, mining, welding & transportation application
- Heavy duty design which permits additional crimp for added mechanical strength




Part No.	WIRE RANGE	STUD HOLE SIZE IN "IN"	COLOUR CODE	DIMENSION IN INCHES					
				A	A1	B	C	E	F
LBL8S	8 Str.	1/4	RED	1.52	0.81	0.42	0.08	0.28	0.59
LBL6S	6 Str.	1/4	BLUE	1.77	0.98	0.42	0.08	0.30	0.67
LBL4S	4 Str.	1/4	GREY	1.77	0.98	0.49	0.09	0.31	0.67
LBL2S	2 Str.	5/16	BROWN	2.07	1.10	0.60	0.10	0.37	0.81
LBL1S	1 Str.	5/16	GREEN	2.11	1.10	0.67	0.11	0.37	0.81
LBL1/0S	1/0 Str.	5/16	PINK	2.21	1.20	0.74	0.13	0.37	0.81
LBL1/0S2	1/0 Str.	3/8	PINK						
LBL2/0S	2/0 Str.	3/8	BLACK	2.66	1.38	0.81	0.12	0.47	1.06
LBL3/0S	3/0 Str.	1/2	ORANGE	2.80	1.38	0.90	0.13	0.47	1.06
LBL4/0S	4/0 Str.	1/2	PURPLE	2.80	1.42	1.00	0.13	0.52	1.06
LBL025S	250 MCM	1/2	YELLOW	3.03	1.61	1.09	0.15	0.52	1.06
LBL030S	300 MCM	1/2	WHITE	3.39	1.97	1.19	0.15	0.52	1.06
LBL035S	350 MCM	1/2	RED	3.46	1.97	1.28	0.17	0.52	1.06
LBL040S1	400 MCM	1/2	BLUE	3.86	1.97	1.39	0.18	0.51	1.38
LBL040S	400 MCM	5/8	BLUE						
LBL050S2	500 MCM	1/2	BROWN	4.13	2.24	1.54	0.22	0.51	1.38
LBL050S	500 MCM	5/8	BROWN						
LBL060S	600 MCM	5/8	GREEN	4.25	2.24	1.72	0.25	0.69	1.46
LBL075S	750 MCM	5/8	BLACK	5.16	2.64	1.90	0.27	0.69	1.85

Approved with Burndy, Thomas and Betts, ILSCO and Huskie Tooling.

K-SPEC® COPPER TWO HOLE SHORT BARREL LUGS

Two-Hole Lug Short Barrel



- Colour coded to show proper die number and colour
- U.L. listed per 486A upto 35kv
- Short barrel designed for regular duty application



Part No.	WIRE RANGE	STUD HOLE SIZE	HOLE SPACING	COLOUR CODE	DIMENSION IN INCHES						
					A	A1	B	C	E	F	G
SBL8D2TC10	8 Str.	10	5/8	RED	1.82	0.44	0.42	0.08	0.28	1.26	0.63
SBL6D2TC14	6 Str.	1/4	5/8	BLUE	2.09	0.71	0.42	0.08	0.28	1.26	0.63
SBL4D2TC14	4 Str.	1/4	5/8	GREY	2.09	0.71	0.49	0.09	0.28	1.26	0.63
SBL2D2TC516E2	2 Str.	5/16	3/4	BROWN	2.62	0.83	0.50	0.10	0.32	1.61	0.75
SBL1D2TC14	1 Str.	1/4	5/8	GREEN	2.28	0.83	0.67	0.11	0.28	1.26	0.63
SBL1/0D2TC516E6	1/0 Str.	5/16	7/8	PINK	2.64	0.83	0.74	0.13	0.32	1.62	0.87
SBL1/0D2TC38	1/0 Str.	3/8	1	PINK	2.83	0.83	0.74	0.13	0.38	1.81	1.00
SBL2/0D2TC38	2/0 Str.	3/8	1	BLACK	2.99	0.94	0.81	0.12	0.38	1.81	1.00
SBL2/0D	2/0 Str.	1/2	1 3/4	BLACK	4.17	0.94	0.81	0.12	0.62	2.99	1.75
SBL3/0D	3/0 Str.	1/2	1 3/4	ORANGE	4.29	0.98	0.90	0.13	0.62	2.99	1.75
SBL4/0D	4/0 Str.	1/2	1 3/4	PURPLE	4.29	0.98	1.00	0.13	0.62	2.99	1.75
SBL4/0D2TC38	4/0 Str.	3/8	1	PURPLE	3.11	0.98	1.00	0.13	0.38	1.81	1.00
SBL025D	250 MCM	1/2	1 3/4	YELLOW	4.41	1.06	1.09	0.15	0.62	2.99	1.75
SBL030D	300 MCM	1/2	1 3/4	WHITE	4.41	1.06	1.19	0.15	0.62	2.99	1.75
SBL035D	350 MCM	1/2	1 3/4	RED	4.53	1.10	1.28	0.17	0.62	2.99	1.75
SBL040D	400 MCM	1/2	1 3/4	BLUE	4.69	1.18	1.39	0.18	0.62	2.99	1.75
SBL050D	500 MCM	1/2	1 3/4	BROWN	4.88	1.38	1.54	0.22	0.62	2.99	1.75
SBL060D2TC38	600 MCM	3/8	1 3/4	GREEN	4.96	1.50	1.72	0.25	0.62	2.99	1.75
SBL060D	600 MCM	1/2	1 3/4	GREEN	5.04	1.50	1.72	0.25	0.62	2.99	1.75
SBL075D	750 MCM	1/2	1 3/4	BLACK	5.51	1.85	1.90	0.27	0.62	2.99	1.75

Approved with Burndy, Thomas and Betts, ILSCO and Huskie Tooling.

