Selection, Service & Quality Solutions

Toll Free 1-800-701-0975 Fax 1-800-892-6360

Toggle Switches (Accessories, Light-Duty & Heavy-Duty)



*765099 Self-Standing Toggle Switch Selector Panel







765001 *765003

765000







765033

765075









765032

765031

765034



765020

Self-Standing Toggle Switch Selector Panel

Use as a Merchandiser/Selection Guide for user to select a toggle switch that suits their needs. Display contains 21 toggle switches with part numbers and specs clearly outlined under each switch

Toggle Switch Accessories

1 no/nk 25 noc/nk

Toggle Boots

EPDM rubber boots with 15/32-32 thread. Provides protection against salt spray and is resistant to weather and ozone. You can use these boots on toggle switches with a 15/32" diameter mounting stem.

	Type	i pc/pk	20 pcs/pk				
	Closed	765001	*765001B	*NEW			
	0pen	*765003	*765003B	* MP -			
Toggle Switch Face Plate							
	Type	1 pc/pk	25 pcs/pk	-181			
	On-Off	765000	*765000B	*NEW			

Looking for a switch that you don't see in this catalogue? We've got a lot more to choose from in our NE Techspan/Pollak catalogue! Ask for it today!

Light-Duty Toggle Switches

The best combination of space-saving size and economy for light-duty applications. Universal for Automotive, Light Truck, Off-road and RV's. Furnished with mounting hardware. CSA approved where shown.

S.P.S.T. (SINGLE POLE - SINGLE THROW) 2 Position (ON-OFF) Switch. Brass construction, screw terminals. Toggles and face nuts are chrome plated. Rating: 6 volt-35 amp, 12 volt-20 amp

Mounting Stem: 3/8" long, 7/16" diameter. 6" leads. CSA approved.

2 Position (OFF-ON) Switch. Nickel-plated 'bat' handle with an on/off indicator and 765072 2 screw terminals. Rating: 6 amps at 125 volts; 3 amps at 250 volts. CSA approved.

Mounting Stem: 15/32" (12 mm) long, 15/32" (12 mm) diameter.

765073 Same as 765072 but with two 6" leads.

Heavy-Duty Toggle Switches

Oversized internal copper contacts will carry up to 50 amp current loads. Provides a long service life. (Note: Bladed terminals will carry 30 amps)

S.P.S.T (SINGLE POLE - SINGLE THROW)

Part No.	Positions	Circuitry	Terminal Type	Amp Rating	Handle Length/Type
765033	2	ON-OFF	2 Blades	30A @ 12VDC	Std. 1" Chrome
765030	2	ON-OFF	2 Screws	50A @ 12VDC	Std. 1" Chrome
765012	2	ON-OFF	2 Screws	50A @ 12VDC	Std. 1" Black
765031	2	ON-OFF	2 Screws	50A @ 12VDC	Long 1 1/2" Chrome

S.P.D.T (SINGLE POLE - DOUBLE THROW)

Part No.	Positions	Circuitry	Terminal Type	Amp Rating	Handle Length/Type
765034	3	ON-OFF-ON	3 Screws	50A @ 12VDC	Std 1" Chrome

Heavy-Duty 'Momentary' Toggle Switches

S.P.D.T (SINGLE POLE - DOUBLE THROW)

Part No.	Positions	Circuitry	Terminal Type	Amp Rating	Handle Length/Type
765032	3	Mom ON-OFF-Mom ON	3 Screws	50A @ 12VDC	Std. 1" Chrome
765020	3	Mom ON-OFF-Mom ON	3 Screws	50A @ 12VDC	Long. 1 1/2" Chrome