



# **CABLE TIE ACCESSORIES**

#### **MOUNTING CRADLE**



- Accepts Cable Ties to 50# Tensile (Miniature through Standard)
- Supplied "Two-Up" on Closed Cell Foam with Synthetic Polymer "Rubber" Based Adhesive
- Use #6 Self-Tapping Screw for added Strength if Desired
- UL Flammability 94 V-2 (mount)
- Mount Molded in 6/6 Natural Nylon





		H Height		L Length		W Width		Slot Height		Slot Width		Mount	Per
Part #	Material	Inch	(mm)	Inch	(mm)	Inch	(mm)	Inch	(mm)	Inch	(mm)	Method	Package
MCNY-1250-9-D	Natural Nylon	.285	(7.24)	1.250	(31.73)	1.000	(25.40)	.090	(2.29)	.300	(7.62)	Adhesive	500
Tolerance ±		.010	(.254)		.015	(.381)			.010	(.254)			

#### K-SPEC® ECONOMY MOUNTING PADS



- 3/4" and 1" Mounts for Use with 18# through 50# Tensile Cable Ties
- Supplied "Two-Up" on Rubber Based (Synthetic Polymer) Closed Cell Foam Adhesive.
- Available in 6/6 Natural Nylon and Black Nylon
- UL Flammability 94 V-2 (clip)

#### Disclaimer

- Not for weight bearing
- For positioning only
- Must be adhered to dry/clean surface

## 3/4" x 3/4" Mount

Part #	Per Package	Material	Mount Method		H ight (mm)	Le Inch	L ength (mm)		W idth (mm)	Slot V	S Width (mm)
ECMP-750-0-C	100	Dis als Nistas								.16	(4.0)
ECMP-750-0-D	500	Black Nylon	Synthetic	.140	(3.5)	.750	(19.04)	.750	(19.04)		
ECMP-750-9-C	100	Notural Nules	Polymer			For us	e with 18-	l -40 lb. C	able Ties		
ECMP-750-9-D	500	Natural Nylon							45.5 1.55		
Tolerance ±				.010	(.254)		.015	(.381)	•	.010	(.254)

### 1" x 1" Mount

Part #	Per Package	Material	Mount Method		H Height Inch (mm)		L Length Inch (mm)		W Width Inch (mm)		S Width (mm)
ECMP-1000-0-C	100	Diggir Nivian									
ECMP-1000-0-D	500	Black Nylon	Synthetic	.16	(4.0)	1.1	(28)	1.1	(28)	.203	(5.16)
ECMP-1000-9-C	100	Nietowel Niedere	Polymer			Foruse	with 18	  -50 lb   Ca	able Ties		
ECMP-1000-9-D	500	Natural Nylon				1 OI USE	WILLI TO	00 ID. 08	ible Hes		
Tolerance ±				.010	(.254)		.015	(.381)		.010	(.254)