

75912	75920	75920-01	880175	880175-0001	880175-0002
2	1	1	2	2	2
2	2	2	2	2	2
No	No	No	No	No	No
No	N/A	N/A	No	No	No
36V DC	36V DC	36V DC	48V DC	48V DC	48V DC
2 X 125A	400A	400A	500A	500A	500A
2x 750A	400A	400A	1000A	1000A	1000A
750A each min.	2,000A	2,000A	2,250A	2,250A	2,250A
2x 1000A	2,000A	2,000A	3,000A (1 sec)	3,000A (1 sec)	3,000A (1 sec)
2/0	4/0	4/0	4/0	4/0	4/0
-40 to +85°C	-40 to +85°C	-40 to +85°C	-50 to +85°C	-50 to +85°C	-50 to +85°C
3/4"-16	3/4"-16	3/4"-16	M12	M12	M12
0.690" (17.5mm)	3/4" (19mm)	3/4" (19mm)	0.984" (25mm)	0.984" (25mm)	0.984" (25mm)
8-10 Nm	8 Nm	8 Nm	30 Nm	30 Nm	30 Nm
Brass	Tin-Plated Copper	Tin-Plated Copper	Tin-Plated Copper	Tin-Plated Copper	Tin-Plated Copper
with 24505	Yes	Yes	Yes	Yes	Yes
Chrome Lever	Red Knob	Yellow Knob	Black Knob	Red Knob	Yellow Knob
No	No	No	SAE J11 & ISO 8846	SAE J11 & ISO 8846	SAE J11 & ISO 8846
IP64	IP68	IP68	IP67 & IP69K	IP67 & IP69K	IP67 & IP69K
3/4"-16	3/4"-16	3/4"-16	N/A	N/A	N/A
Yes	Yes	Yes	-	-	-
					