

# momentary switches

G

HEAVY DUTY PUSH-BUTTON SWITCHES	G1
MEDIUM DUTY PUSH-BUTTON SWITCHES	G2
TWO CIRCUIT PUSH-BUTTON SWITCHES	G3
MARINE CONSTRUCTION PUSH-BUTTON SWITCHES	G4
SPECIAL MOMENTARY SWITCHES	G5
FLEXIBLE CAPS FOR PUSH-BUTTON SWITCHES	G6
DOOR MOMENTARY SWITCHES	G7

## momentary switches

### G1 HEAVY DUTY PUSH-BUTTON SWITCHES

*For applications to 36V DC. Off - On, Normally Off. On with button depressed, spring return to Off. Silver contacts. Chrome plated button and face nut (except where noted).*

#### Cylindrical housing 35A at 12V, 20A at 24V DC.

9095 BP ★



Two screw terminals. Mounting stem: 5/8"-32 thread, 21/32" (16.7mm) long.

#### 9216 with Seal

Same as 9095, except with O-ring seal in the mounting stem.

#### 9216-03 with Seal and Screw-on Cap



Same as 9095, except with O-ring seal in the mounting stem, and screw-on black rubber protective cap (83280-03).

#### 9245 with Seal and Snap-on Cap BP ★



Same as 9095, except with O-ring seal in the mounting stem, snap-on black rubber protective cap (407-03), and black plastic button.

#### 90036-02 with blade terminals



Same as 9095, except with 2 blade terminals to fit Delphi (Packard) 2973407 two-way connectors, or similar.

#### 9244-02\* with Seal, Screw-on Cap, Stud Terminals

Same as 9095, except with O-ring seal in the mounting stem and screw-on black rubber protective cap (83280-03), two 10-32 stud terminals with hexnuts and lockwashers, and black plastic button.

CONTINUED **G1**

# G momentary switches

G1 HEAVY DUTY PUSH-BUTTON SWITCHES

## 9155\* with large button



15/16" diameter button. 2 screw terminals with lockwashers. Mounting stem: 5/8"-32 thread, 21/32" (16.7mm) long.

## 9231 with protected button ★



With recessed facenut designed to prevent accidental actuation. 2 screw terminals. Mounting stem: 5/8"-32 thread, 21/32" (16.7mm) long.

## 90000-01\* with protected button, and seal

Same as 9231, except with O-ring seal in the mounting stem.

## 90030 with plastic button, and screw-on cap BP ★



Two screw terminals. Mounting stem: 5/8"-32 thread, 21/32" (16.7mm) long. With screw-on black rubber protective cap 83280-03.

## 90030-01 with plastic button, and oil-resistant cap

Same as 90030, except with brown oil-resistant cap 83280-05.

## 90030-04 with plastic button, and red screw-on cap

Same as 90030, except with Red screw-on protective cap 83280-02.

## 90011\* with plastic button, and button terminals



Two male button head terminals, accept Delphi (Packard) connector 2962679, or equivalent. Mounting stem: 5/8"-32 thread, 5/8" (15.9mm) long. Accepts screw-on protective cap 83280-03. Black plastic button.

## Rectangular housing

10A at 12V DC, except where noted.

9044



2 screw terminals. Mounting stem: 5/8"-32 thread, 1.06" (26.9mm) long. Gasket seal in the case.

## 9044-02\* with cap

Same as 9044, but with screw-on black rubber protective cap 83280-03.

## 9023 ★



15A resistive, 10A inductive at 12V DC, 8A resistive, 5A inductive at 24V DC. Two screw terminals. Mounting stem: 5/8"-32 thread, .87" (22.1mm) long.

## 9023-09 with cap

Same as 9023, but with screw-on black rubber protective cap 83280-03.

## 9238 with blade terminals ★

Same as 9023, but with blade terminals.

## 9238-01 with blade terminals, and cap

Same as 9023, but with blade terminals and black rubber screw-on cap 83280-03.

## 9023-A\* with silver contacts

Same as 9023, but with silver contacts, giving greater voltage range – 6-36V DC. 15A at 12V, 8A at 24V, 4A at 36V DC.

## more moms

You'll find more moms (or momentary switches) in the following catalog sections:

Rocker Switches – Section A  
Toggle Switches – Section B  
Ignition Switches – Section C  
Rotary Switches – Section D

★ Rapid ship item. BP Available in retail clamshell pack. ★ Minimum order quantity may apply.