

G2 MEDIUM DUTY PUSH-BUTTON SWITCHES

9115 ★




Two screw terminals with lockwashers. Mounting stem: 5/8"-32, 7/8" thread (22.2mm) long.

90028*

Same as 9115, but with blade terminals.

90002 sealed



Weather-resistant and dust-resistant. Gasket-sealed case and O-ring in stem. Two screw terminals with lockwashers. Mounting stem: 5/8"-32 thread, 1 1/16" (26.9mm) long.

90002-01 sealed, heavy-duty

Same as 90002, except with silver contacts for heavy duty applications up to 36V DC.

91126 PVC-coated



PVC-coated body for moisture and dirt protection. Two 7" (177.8mm) wire leads. Mounting stem: 7/16"-20 thread, .44" (11.2mm) long. Steel button, .38" (9.7mm) diameter.

90043 sealed, with rubber cap ★



Two blade terminals accept 2-pole Delphi (Packard) connector 2977647 or equivalent. Mounting stem: 5/8"-32 thread, .625" (15.9mm) long. Gasket seal in the case. Steel plunger protrudes through the cap. Black rubber cap snaps into a special groove on the nut, which is deep-threaded and gives a positive seal.

90043-07 PVC-coated, sealed, with rubber cap ★



Same as 90043, except with PVC-coated body and two 7" (177.8mm) 18AWG wire leads.

9212



2 blade terminals. Mounting stem: 7/16"-20 thread, 1/2" (12.7mm) long. 1/2" (12.7mm) plunger with nylon cap.

momentary switches


G3 TWO CIRCUIT PUSH-BUTTON SWITCHES

Two circuits are simultaneously energized.

Normally Off

Off-On, normally Off. On with plunger depressed, spring return to Off.

9165 with screw terminals



10A per circuit at 12V DC. Three screw terminals with lockwashers. Mounting stem: 5/8"-32 thread, 21/32" (16.7mm) long with two steel hexnuts and facenut.

9276* with blade terminals, silver contacts



35A at 12V, 20A at 24V, 10A at 36V DC. Three blade terminals. Mounting stem: 5/8"-32 thread, 21/32" (16.7mm) long. Silver contacts for extra-heavy applications to 36V DC.

CONTINUED **G3**

★ Rapid ship item. BP Available in retail clamshell pack. ★ Minimum order quantity may apply.