

# G momentary switches

## G5 SPECIAL MOMENTARY SWITCHES

### 9011 Normally Off



Plated steel button, aluminum body. Two screw terminals, 7/8" -20 mounting stem, 3/8" (9.5mm) long.

### 9105 Toggled



10A at 12V, 5A at 24V. Two 6" (152.4mm) wire leads, 16AWG (1.00mm<sup>2</sup>). Phenolic body, 1.080"L x .530"W x 1.10"H (27.4 x 13.5 x 28.0mm). Push-button diameter .410" (10.4mm). Stem: .470" long (11.9mm). Can be used as a foot switch in dry environments.

### 9187 Normally Off, Black button **BP**



5A at 12V to 24V DC. Two blade terminals .250" wide (6.4mm). Nickel-plated brass hexnut and facenut. Nylon push-button, .410" diameter (10.4mm). Body size (to top of terminal): .890"L x .560"W x .773"H (22.6 x 14.2 x 19.6mm).

### 9187-01 Normally Off, White button **BP**

Same as 9187, except with white/natural nylon color button.

### 9187-02 Normally Off, Red button **BP**

Same as 9187, except with red button.

# momentary switches

## G6 CAPS FOR PUSH BUTTON SWITCHES

*Flexible caps give added resistance to weather and dust.*

### Threaded Caps

Rubber cap is permanently fastened to the integral mounting nut by a rolled brass bezel. The deep threaded 5/8"-32 aluminum mounting nut assures a positive seal. Durable, resilient rubber, embossed 'PUSH'. Fits Cole Hersee and all other push button switches with a 5/8"-32 thread mounting stem.

### 83280-03 Black **BP**

### 83280 Gray

### 83280-02 Red



### 83280-05 Oil-resistant

For use on fuel delivery trucks. Cap is molded from resilient Hydrin which provides excellent resistance to fuel oils. Brown color.

### Snap-on Caps

Ribs on the inside of the rubber cap engage with the switch facenut. Facenut – Section S2.

### 407-03 Black **BP**

### 407-01 Gray **BP**



★ Rapid ship item. **BP** Available in retail clamshell pack. ★ Minimum order quantity may apply.



Cole Hersee Co. 20 Old Colony Ave, Boston, MA 02127-2467

70

T 617.268.2100 F 617.268.9490 www.colehersee.com