



## DL Series • 12V Single Contact, Grounding Pilot Lights

- Self-grounding to metal panels
- · For illumination of maps or other items, with minimal interference of driving visibility
- Hood can be rotated to direct the light beam
- 11/16" (17.5mm) diameter mounting stem, 3/8" (9.5mm) long; mount through the panel.
- 16AWG insulated stranded copper leads
- Suggested lamps (not included): #63 (6V), #67 (12V), #623 (24V).



PART NUMBERS			RATING	COLOR	MATERIAL	TERMINALS
BULK	BOXED	RETAIL	IIAIIINO	COLON		TERMINALO
DL-13	DL-13-BX	_	12V DC	Chrome-plated	Brass	1x 8" wire leads
DL-21	DL-21-BX	-	12V DC	Black	Steel	1x 8" wire leads

## 12V Bayonet Base Sockets

- Accept incandescent or LED bulbs with corresponding bases.
- Suggested lamp numbers for BA15s sockets: 63, 67, 81, 87, 93, 97,103, 209,1073, 1129, 1133, 1141, 1156.
- 16AWG insulated stranded copper leads 8" (203mm) long



26145







PART NUMBERS BULK BOXED RETAIL		RATING	LAMPS ACCEPTED	MOUNTING	TERMINALS	CONTACT TYPE	NOTES	
26145	-	-	12V DC	BA15s	-	2x 8" wire lead (Ground Wire)	Single	For back-up, tail, stop, turn signal & corner lights. Replaces: GMC 8909518, International 57121C91, Motorcraft LS-22.
2609	2609-BX	-	12V DC	BA15s	Side bracket with 3/16" (4.8mm) Ø hole	1x 8" wire lead	Single	-
3575	3575-BX	-	12V DC	BA15s	Bottom bracket with two 13/64" (5.2mm) Ø holes, ½" (12.7mm) on centers	1x 8" wire lead	Single	-
2611*	-	-	12V DC	BA15s	¾" (19.0mm) Ø hole	1x 8" wire lead	Single	_
2612*	-	-	12V DC	BA15d	¾" (19.0mm) Ø hole	2x 8" wire leads	Double	-



2505



2506





\*Special Order Item

Suggested lamp numbers: 51 (6V), 53 (12V), 356 (24V).
Plated steel sockets

PART NUMBERS			RATING	LAMPS	MOUNTING	TERMINALS	CONTACT	NOTES
BULK	BOXED	RETAIL	IIAIINO	ACCEPTED	WOONTING	TERIVINALO	TYPE	NOTES
2505	2505-BX	-	12V DC	BA9	5/8" (15.9mm) Ø hole	1x 8" wire leads	Single	Socket spacer rings to fit other panel thicknesses available
2506	2506-BX	-	12V DC	BA9	5/8" (15.9mm) Ø hole	2x 8" wire leads	Single	Ground lead attached to shell

## **Pigtail Assemblies**

- For different lead lengths, colors and materials, please contact Littelfuse
- Leads are made from high quality 16AWG (1.0mm2) thermoplastic jacketed wire.
- Phenolic washers insulate the assemblies.

Miniature Base Sockets - Single Contact

PART NUMBERS			CONTACT TYPE	FITS SOCKET PART NUMBERS	NOTES	
BULK	BOXED	RETAIL			110120	
2560	2560-BX	-	Single	2601, 2609, 2611, 2645, 2670, 3575, 26003, 26041.	-	
2564	2564-BX	-	Double	2602, 2608, 2610, 2612, 26041.	Ears in line with contacts	