

CABLE SUPPORT GRIPS

Heavy Duty support grips made from stainless steel are perfect for supporting heavier cable, conduit or any other cylindrical object. Often used by Utilities and Contractors to support cables transitioning from overhead to underground. One may support multiple cables in one grip. The overall diameter of the cable bundle should fit within the listed range.



HEAVY DUTY SUPPORT GRIPS - SINGLE EYE

Slingco Part No	Range		Approx. Break Load	
	in	mm	lb	kg
ZCS7065	0.50 - 0.63	13 - 16	1,370	621
ZCS7066	0.63 - 0.75	16 - 19	2,060	944
ZCS7067	0.75 - 1.00	19 - 25	2,060	944
ZCS7068	1.00 - 1.25	25 - 32	2,678	1,216
ZCS7069	1.25 - 1.50	32 - 38	4,490	2,037
ZCS7070	1.50 - 1.75	38 - 44	4,490	2,037
ZCS7071	1.75 - 2.00	44 - 51	5,000	2,269
ZCS7072	2.00 - 2.50	51 - 63	8,940	4,056
ZCS7073	2.50 - 3.00	63 - 76	8,940	4,056
ZCS7074	3.00 - 3.50	76 - 87	13,420	6,089
ZCS7075	3.50 - 4.00	87 - 102	13,420	6,089

HEAVY DUTY SUPPORT GRIPS - DOUBLE EYE

Slingco Part No	Range		Approx. Break Load	
	in	mm	lb	kg
ZCS3057	0.50 - 0.63	13 - 16	1,370	621
ZCS3058	0.63 - 0.75	16 - 19	2,080	944
ZCS3059	0.75 - 1.00	19 - 25	2,080	944
ZCS3060	1.00 - 1.25	25 - 31	2,870	1,302
ZCS3061	1.25 - 1.50	31 - 38	4,490	2,037
ZCS3062	1.50 - 1.75	38 - 44	4,490	2,037
ZCS3063	1.75 - 2.00	44 - 50	5,000	2,268
ZCS3064	2.00 - 2.50	50 - 63	8,940	4,056
ZCS3065	2.50 - 3.00	63 - 76	8,940	4,056
ZCS3066	3.00 - 3.50	76 - 89	12,000	5,445
ZCS3067	3.50 - 4.00	89 - 102	12,000	5,445

HEAVY DUTY SUPPORT GRIPS - SINGLE EYE ROD CLOSING

Slingco Part No	Range		Approx. Break Load	
	in	mm	lb	kg
ZCS7076	0.50 - 0.63	13 - 16	1370	621
ZCS7077	0.63 - 0.75	16 - 19	2080	944
ZCS7078	0.75 - 1.00	19 - 25	2080	944
ZCS7079	1.00 - 1.25	25 - 32	2670	1211
ZCS7080	1.25 - 1.50	32 - 38	4490	2037
ZCS7081	1.50 - 1.75	38 - 44	4490	2037
ZCS7082	1.75 - 2.00	44 - 51	5000	2269
ZCS7083	2.00 - 2.50	51 - 63	8940	4056
ZCS7084	2.50 - 3.00	63 - 76	8940	4056
ZCS7085	3.00 - 3.50	76 - 87	13420	6089
ZCS7086	3.50 - 4.00	87 - 102	13420	6089

HEAVY DUTY SUPPORT GRIPS - DOUBLE EYE ROD CLOSING

Slingco Part No	Range		Approx. Break Load	
	in	mm	lb	kg
ZCS7098	0.50 - 0.63	13 - 16	1,370	621
ZCS7099	0.63 - 0.75	16 - 19	2,080	944
ZCS7100	0.75 - 1.00	19 - 25	2,080	944
ZCS7101	1.00 - 1.25	25 - 32	2,670	1,211
ZCS7102	1.25 - 1.50	32 - 38	4,490	2,037
ZCS7103	1.50 - 1.75	38 - 44	4,490	2,037
ZCS7104	1.75 - 2.00	44 - 51	5,000	2,269
ZCS7105	2.00 - 2.50	51 - 63	8,940	4,056
ZCS7106	2.50 - 3.00	63 - 76	8,940	4,056
ZCS7107	3.00 - 3.50	76 - 87	13,420	6,089
ZCS7108	3.50 - 4.00	87 - 102	13,420	6,089