




Heyco® Knock-Out Seals

MOUNTING HOLE DIAMETER		TRADE SIZE	PART NO. Silver Gray	DESCRIPTION	PART DIMENSIONS			
in.	mm.				A Head Diameter		B Overall Height	
Multiple Locking Steps for Panel Thickness up to .125" (3,2 mm)								
.875	22,2	1/2	3997	KOS 1/2	1.02	25,8		
1.093	27,8	3/4	3998	KOS 3/4	1.22	31,0		
1.375	34,9	1	3999	KOS 1	1.50	38,1	.45	11,5
1.750	44,5	1-1/4	4000	KOS 1-1/4	1.91	48,4		
2.000	50,8	1-1/2	4001	KOS 1-1/2	2.16	54,9		
Multiple Locking Steps for Panel Thickness up to .250" (6,4 mm)								
2.500	63,5	2	4002	KOS 2	2.73	69,3	.75	19,1

Standard color silver gray.



- Plug electrical knock-outs.
- Molded in silver gray color to resemble galvanized steel.
- Install quickly with fingertip pressure (no tool required).
- Economical.
- Multiple trade sizes fit 1/2" to 2" knock-out holes.
- Lock firmly in boxes up to 1/8" thick, except for Part Number 4002 (KOS 2) and Thick Panel Knock-Out Seals (KOST's) which lock firmly in boxes up to 1/4" thick.
- Locking fingers in fractional increments up to the maximum panel thickness.
- Approximate Head Thickness: .062" (1,6 mm). Thickness may vary.
- To adapt a Knock-Out to accept a Heyco Strain Relief, see Heyco Knock-Out Adapters on page 4-37.

Heyco® Thick Panel Knock-Out Seals

MOUNTING HOLE DIAMETER		TRADE SIZE	PART NO. Silver Gray	DESCRIPTION	PART DIMENSIONS			
in.	mm.				A Head Diameter		B Overall Height	
Multiple Locking Steps for Panel Thickness up to .250" (6,4 mm)								
.875	22,2	1/2	3991	KOST 1/2	1.02	25,8		
1.093	27,8	3/4	3992	KOST 3/4	1.22	31,0	.56	14,3
1.375	34,9	1	3993	KOST 1	1.50	38,1		
1.750	44,5	1-1/4	3994	KOST 1-1/4	1.91	48,4		
2.000	50,8	1-1/2	3995	KOST 1-1/2	2.16	54,9	.58	14,7
2.500	63,5	2	4002	KOS 2	2.73	69,3	.75	19,1

Standard color silver gray.



Material	Nylon 6/6
Certifications	Recognized under the Component Program of Underwriters' Laboratories, File E51579
	Certified by Canadian Standards Association, File 8919
Flammability Rating	94V-2
Material Temperature Index	275°F (125°C)–Maximum temperature on part not to exceed 221°F (105°C)

Quick Specs