

Mechanical Compression Tool with Rotating Dies TDM408

- Comfort grip handles reduce fatigue during continuous use
- Compression connectors are UL listed and CSA certified when installed in accordance with manufacturer's installation instructions
- Crimps all popular small to mid-range copper lugs and splices
- Built-in rotatable dies eliminate need to carry and maintain nine sets of dies
- Plated jaws ensure protection against corrosion



For use with: BLU, BBLU, BBLZ, BCU, BBCU and BCUR style copper connectors

CAPACITY: 8 - 4/0 AWG Copper Only

LENGTH: 24.4 in. **WEIGHT:** 8.8 lbs.

Mechanical Compression Tool TMUOD3

- Die inserts snap into the D3 groove with one hand and are locked into the tool with spring loaded positive lock die retainer buttons
- Versatile mechanical compression tool for full tension and non-tension splices
- Over center cam action
- High strength, butting, forged steel jaws
- Provides 4.5 tons of crimping force
- No additional dies required for "O" and "D3" size tap connectors; D3 Groove accommodates full line of industry standard "W" die inserts
- Bent handles and anti-slip grips for easier operation
- Tool adjustment easily checked and adjusted with allen wrench



For use with: CCT, CST and CDT style copper connectors; KO, KD, PIK, PSK, PSKS and DBTBF style aluminum connectors

CAPACITY: 14 - 4/0 AWG

LENGTH: 25.5 in. **WEIGHT:** 9.0 lbs.

Mechanical Ratchet Hand Crimp Tool TRC28

- For insulated and non-insulated terminals, and Type "RTC" copper C-Taps (RTC-2 through RTC-6)
- Full cycle ratcheting mechanism ensures proper crimp



CAPACITY: Insulated terminals 8 - 2 AWG;
Non-insulated terminals 6 - 1/0 AWG

LENGTH: 16.1 in. **WEIGHT:** 4.6 lbs.