

Loom & Tubing

High Temperature Convoluted Tubing/ Split Loom (Nylon)

Nylon Convoluted Tubing/Split Loom has a temperature rating of 300°F (149°C) making it suitable for applications such as inside engine compartments, etc. Identified by its grey stripe.

Small Packaging – (Rolled neatly in bags)

ID Size	50FT Roll	Package Type
1/4"	769901	Bag
3/8"	769902	Bag
1/2"	769903	Bag
5/8"	769904	Bag
3/4"	769905	Bag
1"	769906	Bag

Bulk Packaging – (Continuous Roll in a Box)

ID Size	Part#	Package Quantity	Packaging Type
1/4"	769901B	1 x3200FT	Box
3/8"	769902B	1 x1900FT	Box
1/2"	769903B	1 x1100FT	Box
5/8"	769904B	1 x 800FT	Box
3/4"	769905B	1 x 550FT	Box
1"	769906B	1 x 300FT	Box
1-1/4"	769907B	1 x 250FT	Box
1-1/2"	769908B	1 x 150FT	Box
2"	769910B	1 x 100FT	Box



DID YOU KNOW?

High Temperature (Nylon) Convoluted Tubing/
Split Loom is identified by having a grey stripe
across the length of the tubing.

Nylon
material allows
for applications
up to 300°F
(149°C)



High Temperature Convoluted Tubing/Split Loom (Nylon)



High Temperature Convoluted Tubing/Split Loom (Nylon) in
a Bulk Box

Convoluted Tubing/Split Loom Installation Tools

For quick & easy installation of Split Loom!

Size Range	Part#
1/4", 3/8"	769828
1/2", 5/8"	769829
3/4"	769830
1", 1-1/4"	769831
1-1/2", 2"	769832



Convoluted Tubing/Split Loom Installation Tools

Product Dimensions

Nominal ID Diameter	Dia. Code	Units	Dimension "A"		Dimension "B"		Dim. "C" Wall Min	Dim. (E) Corr Ht. Ref.
			ID		OD			
			Min	Max.	Min	Max.		
1/4"	07L	mm	6.50	7.01	9.47	10.11	0.11	1.52
(7 mm)		Inches	0.256	0.276	0.373	0.398	0.004	0.060
3/8"	038	mm	8.66	9.65	12.59	13.36	0.12	1.91
(9 mm)		Inches	0.341	0.380	0.496	0.526	0.005	0.075
1/2"	012	mm	12.01	13.11	16.87	17.78	0.12	2.38
(13 mm)		Inches	0.473	0.516	0.664	0.700	0.005	0.094
5/8"	058	mm	15.32	16.23	20.36	21.26	0.12	2.45
(16 mm)		Inches	0.603	0.639	0.802	0.837	0.005	0.099
3/4"	034	mm	17.96	19.28	24.13	25.12	0.12	3.00
(19 mm)		Inches	0.707	0.759	0.950	0.989	0.005	0.118
1"	100	mm	25.91	27.16	31.78	33.13	0.15	2.96
(25 mm)		Inches	1.020	1.069	1.251	1.304	0.006	0.117
1 1/4"	114	mm	30.45	31.93	36.73	38.10	0.15	3.11
(30 mm)		Inches	1.199	1.257	1.446	1.500	0.006	0.123
1 1/2"	112	mm	39.78	41.83	47.42	49.45	0.15	3.82
(40 mm)		Inches	1.566	1.647	1.867	1.947	0.006	0.150
2"	200	mm	50.01	51.77	58.04	60.66	0.28	4.23
(51 mm)		Inches	1.969	2.038	2.285	2.388	0.011	0.167
2 1/2"	212	mm	62.15	63.90	70.39	73.01	0.28	4.34
(64 mm)		Inches	2.447	2.516	2.771	2.874	0.011	0.171

