

SWIVEL & CONNECTOR REPLACEMENT PINS



KEY FEATURES

- ✓ Pins to suit our connector link
- ✓ High Strength

Replacement pins for the popular connectors.

Swivel or Connector Model	Replacement Pin (HEX)	Replacement Pin (Slotted)
ZSW2091	SWI2859	SWI2331
ZSW2092	SWI2810	SWI2332
ZSW2093	SWI2339	SWI2333-T
ZSW2094	SWI2341	SWI2334
ZSW2096, ZSW6122	SWI2343	SWI3571
ZSW2097	SWI2344	SWI3565
ZSW2929	SWI2801	SWI2802
ZSW2649	SWI2648	SWI2646
ZSW2857	SWI2748	SWI3429
ZSW6123	SWI5184	
ZSW6554	SWI2859	
ZSW6555	SWI2339	
ZSW6556	SWI5309	
ZSW6557, ZSW6558, ZSW6559, ZSW6560	SWI5310	

Note

All Slingco Line Pulling Swivels are designed for straight line pulling and will not support side loads as would be encountered traveling over a bull wheel. Swivel selection should be based on pulling line diameter, grip size, opening dimensions, pin sizes, working load, and sheave groove diameter. Swivels are not designed for general lifting.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco America, Inc.

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-5%. Please contact us if you have any questions.

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.