

# TERMINALS & CONNECTORS (K-SPEC® SERIES)

## PVC Insulated Bullet Connectors (K-Spec® Series)

300V Rating, 167°F (75°C), Brass



### 22-18GA



.156" Female Receptacle

561248	100 pk
561248D	500 pk



.156" Male Snap Plug

561247	100 pk
561247D	500 pk

### 16-14GA - 2 Way (Clear)



NOT LISTED

Mates with two .156" Males

691261	5 pk
561261	100 pk
561261D	500 pk

### 16-14GA



.156" Female Receptacle

691289	8 pk
561289	100 pk
561289D	500 pk



.156" Male Snap Plug

691251	8 pk
561251	100 pk
561251D	500 pk



.197" Female Receptacle

561258	100 pk
561258D	500 pk



.197" Male Snap Plug

561257	100 pk
561257D	500 pk

### 12-10GA



.197" Female Receptacle

561260	100 pk
561260D	500 pk



.197" Male Snap Plug

561259	100 pk
561259D	500 pk

## PVC Insulated Piggy Back Connectors (K-Spec® Series)

300V Rating, 167°F (75°C), Brass



### 22-18GA



562415	100 pk
562415D	500 pk

### 16-14GA



562416	100 pk
562416D	500 pk

### 12-10GA



562399	100 pk
562399D	500 pk

## PVC Insulated Instant Connectors (K-Spec® Series)

600V Rating, 167°F (75°C), Copper



NOT LISTED

### 22-18GA



Tap Splice-Red

561370	100 pk
561370D	500 pk

### 16-14GA



Tap Splice-Blue

691371	3 pk
561371	100 pk
561371D	500 pk

### 12-10GA



Tap Splice-Yellow

691372	2 pk
561372	100 pk
561372D	500 pk

## PVC Insulated Pin Terminals (K-Spec® Series)

600V Rating, 167°F (75°C), Copper



### 22-18GA



562418	100 pk
562418D	500 pk

### 16-14GA



562419	100 pk
562419D	500 pk

### 12-10GA



562417	100 pk
562417D	500 pk