

K-SPEC® HEAT SHRINK TUBING



CROSS-LINK POLYOLEFIN

- CSA Approved
- Flame Retardant (except Clear)
- Thin Wall 2:1 Ratio
- Oper. Temp.: -49°F to 257°F (-45°C to 125°C)
- Shrink Temp.: Start at 158°F (70°C), recovery at 248°F (120°C)
- Longitudinal shrink ratio: < or = 8%
- 600V rated
- UL224 VW-1 – black only
- Low smoke generation
- Zero halogen



Part No.	DESCRIPTION 4 FOOT PIECES	CTN/ QTY
MHSP-3/64-0-IIL	HEAT SHRINK THIN-WALL BLACK 3/64"ID X 4FT	50 PK
MHSP-3/64-2-IIL	HEAT SHRINK THIN-WALL RED 3/64"ID X 4FT	50 PK
MHSP-3/64-4-IIL	HEAT SHRINK THIN-WALL YELLOW 3/64"ID X 4FT	50 PK
MHSP-3/64-5-IIL	HEAT SHRINK THIN-WALL GREEN 3/64"ID X 4FT	50 PK
MHSP-3/64-6-IIL	HEAT SHRINK THIN-WALL BLUE 3/64"ID X 4FT	50 PK
MHSP-3/64-9-IIL	HEAT SHRINK THIN-WALL CLEAR 3/64"ID X 4FT	50 PK
MHSP-3/64-WH-IIL	HEAT SHRINK THIN-WALL WHITE 3/64"ID X 4FT	50 PK
MHSP-1/16-0-IIL	HEAT SHRINK THIN-WALL BLACK 1/16"ID X 4FT	50 PK
MHSP-1/16-2-IIL	HEAT SHRINK THIN-WALL RED 1/16"ID X 4FT	50 PK
MHSP-1/16-4-IIL	HEAT SHRINK THIN-WALL YELLOW 1/16"ID X 4FT	50 PK
MHSP-1/16-5-IIL	HEAT SHRINK THIN-WALL GREEN 1/16"ID X 4FT	50 PK
MHSP-1/16-6-IIL	HEAT SHRINK THIN-WALL BLUE 1/16"ID X 4FT	50 PK
MHSP-1/16-9-IIL	HEAT SHRINK THIN-WALL CLEAR 1/16"ID X 4FT	50 PK
MHSP-1/16-WH-IIL	HEAT SHRINK THIN-WALL WHITE 1/16"ID X 4FT	50 PK
MHSP-3/32-0-IIL	HEAT SHRINK THIN-WALL BLACK 3/32"ID X 4FT	50 PK
MHSP-3/32-2-IIL	HEAT SHRINK THIN-WALL RED 3/32"ID X 4FT	50 PK
MHSP-3/32-4-IIL	HEAT SHRINK THIN-WALL YELLOW 3/32"ID X 4FT	50 PK
MHSP-3/32-5-IIL	HEAT SHRINK THIN-WALL GREEN 3/32"ID X 4FT	50 PK
MHSP-3/32-6-IIL	HEAT SHRINK THIN-WALL BLUE 3/32"ID X 4FT	50 PK
MHSP-3/32-9-IIL	HEAT SHRINK THIN-WALL CLEAR 3/32"ID X 4FT	50 PK
MHSP-3/32-WH-IIL	HEAT SHRINK THIN-WALL WHITE 3/32"ID X 4FT	50 PK
MHSP-1/8-5-IIL	HEAT SHRINK THIN-WALL GREEN 1/8"ID X 4FT	50 PK
MHSP-1/8-6-IIL	HEAT SHRINK THIN-WALL BLUE 1/8"ID X 4FT	50 PK
MHSP-1/8-9-IIL	HEAT SHRINK THIN-WALL CLEAR 1/8"ID X 4FT	50 PK
MHSP-1/8-WH-IIL	HEAT SHRINK THIN-WALL WHITE 1/8"ID X 4FT	50 PK
MHSP-1/4-0-IIL	HEAT SHRINK THIN-WALL BLACK 1/4"ID X 4FT	25 PK
MHSP-1/4-2-IIL	HEAT SHRINK THIN-WALL RED 1/4"ID X 4FT	25 PK
MHSP-1/4-4-IIL	HEAT SHRINK THIN-WALL YELLOW 1/4"ID X 4FT	25 PK
MHSP-1/4-9-IIL	HEAT SHRINK THIN-WALL CLEAR 1/4"ID X 4FT	25 PK
MHSP-1/4-WH-IIL	HEAT SHRINK THIN-WALL WHITE 1/4"ID X 4FT	25 PK
MHSP-3/16-0-IIL	HEAT SHRINK THIN-WALL BLACK 3/16"ID X 4FT	50 PK
MHSP-3/16-2-IIL	HEAT SHRINK THIN-WALL RED 3/16"ID X 4FT	50 PK
MHSP-3/16-4-IIL	HEAT SHRINK THIN-WALL YELLOW 3/16"ID X 4FT	50 PK
MHSP-3/16-5-IIL	HEAT SHRINK THIN-WALL GREEN 3/16"ID X 4FT	50 PK
MHSP-3/16-6-IIL	HEAT SHRINK THIN-WALL BLUE 3/16"ID X 4FT	50 PK
MHSP-3/16-WH-IIL	HEAT SHRINK THIN-WALL WHITE 3/16"ID X 4FT	50 PK
MHSP-5/16-0-IIL	HEAT SHRINK THIN-WALL BLACK 5/16"ID X 4FT	25 PK
MHSP-5/16-2-IIL	HEAT SHRINK THIN-WALL RED 5/16"ID X 4FT	25 PK
MHSP-5/16-5-IIL	HEAT SHRINK THIN-WALL GREEN 5/16"ID X 4FT	25 PK
MHSP-5/16-6-IIL	HEAT SHRINK THIN-WALL BLUE 5/16"ID X 4FT	25 PK
MHSP-5/16-9-IIL	HEAT SHRINK THIN-WALL CLEAR 5/16"ID X 4FT	25 PK
MHSP-5/16-WH-IIL	HEAT SHRINK THIN-WALL WHITE 5/16"ID X 4FT	25 PK
MHSP-3/8-0-IIL	HEAT SHRINK THIN-WALL BLACK 3/8"ID X 4FT	25 PK
MHSP-3/8-2-IIL	HEAT SHRINK THIN-WALL RED 3/8"ID X 4FT	25 PK
MHSP-3/8-4-IIL	HEAT SHRINK THIN-WALL YELLOW 3/8"ID X 4FT	25 PK
MHSP-3/8-5-IIL	HEAT SHRINK THIN-WALL GREEN 3/8"ID X 4FT	25 PK
MHSP-3/8-6-IIL	HEAT SHRINK THIN-WALL BLUE 3/8"ID X 4FT	25 PK
MHSP-3/8-9-IIL	HEAT SHRINK THIN-WALL CLEAR 3/8"ID X 4FT	25 PK
MHSP-3/8-WH-IIL	HEAT SHRINK THIN-WALL WHITE 3/8"ID X 4FT	25 PK

Part No.	DESCRIPTION 4 FOOT PIECES	CTN/ QTY
MHSP-1/2-0-IIL	HEAT SHRINK THIN-WALL BLACK 1/2"ID X 4FT	25 PK
MHSP-1/2-2-IIL	HEAT SHRINK THIN-WALL RED 1/2"ID X 4FT	25 PK
MHSP-1/2-4-IIL	HEAT SHRINK THIN-WALL YELLOW 1/2"ID X 4FT	25 PK
MHSP-1/2-5-IIL	HEAT SHRINK THIN-WALL GREEN 1/2"ID X 4FT	25 PK
MHSP-1/2-6-IIL	HEAT SHRINK THIN-WALL BLUE 1/2"ID X 4FT	25 PK
MHSP-1/2-9-IIL	HEAT SHRINK THIN-WALL CLEAR 1/2"ID X 4FT	25 PK
MHSP-1/2-WH-IIL	HEAT SHRINK THIN-WALL WHITE 1/2"ID X 4FT	25 PK
MHSP-5/8-0-IIL	HEAT SHRINK THIN-WALL BLACK 5/8"ID X 4FT	25 PK
MHSP-5/8-2-IIL	HEAT SHRINK THIN-WALL RED 5/8"ID X 4FT	25 PK
MHSP-5/8-4-IIL	HEAT SHRINK THIN-WALL YELLOW 5/8"ID X 4FT	25 PK
MHSP-5/8-5-IIL	HEAT SHRINK THIN-WALL GREEN 5/8"ID X 4FT	25 PK
MHSP-5/8-6-IIL	HEAT SHRINK THIN-WALL BLUE 5/8"ID X 4FT	25 PK
MHSP-5/8-9-IIL	HEAT SHRINK THIN-WALL CLEAR 5/8"ID X 4FT	25 PK
MHSP-5/8-WH-IIL	HEAT SHRINK THIN-WALL WHITE 5/8"ID X 4FT	25 PK
MHSP-3/4-0-IIL	HEAT SHRINK THIN-WALL BLACK 3/4"ID X 4FT	10 PK
MHSP-3/4-2-IIL	HEAT SHRINK THIN-WALL RED 3/4"ID X 4FT	10 PK
MHSP-3/4-4-IIL	HEAT SHRINK THIN-WALL YELLOW 3/4"ID X 4FT	10 PK
MHSP-3/4-5-IIL	HEAT SHRINK THIN-WALL GREEN 3/4"ID X 4FT	10 PK
MHSP-3/4-6-IIL	HEAT SHRINK THIN-WALL BLUE 3/4"ID X 4FT	10 PK
MHSP-3/4-9-IIL	HEAT SHRINK THIN-WALL CLEAR 3/4"ID X 4FT	10 PK
MHSP-3/4-WH-IIL	HEAT SHRINK THIN-WALL WHITE 3/4"ID X 4FT	10 PK
MHSP-1-0-IIL	HEAT SHRINK THIN-WALL BLACK 1"ID X 4FT	10 PK
MHSP-1-2-IIL	HEAT SHRINK THIN-WALL RED 1"ID X 4FT	10 PK
MHSP-1-4-IIL	HEAT SHRINK THIN-WALL YELLOW 1"ID X 4FT	10 PK
MHSP-1-5-IIL	HEAT SHRINK THIN-WALL GREEN 1"ID X 4FT	10 PK
MHSP-1-6-IIL	HEAT SHRINK THIN-WALL BLUE 1"ID X 4FT	10 PK
MHSP-1-9-IIL	HEAT SHRINK THIN-WALL CLEAR 1"ID X 4FT	10 PK
MHSP-1-WH-IIL	HEAT SHRINK THIN-WALL WHITE 1"ID X 4FT	10 PK
MHSP-1-1/4-0-IIL	HEAT SHRINK THIN-WALL BLACK 1-1/4"ID X 4FT	5 PK
MHSP-1 1/2-0-IIL	HEAT SHRINK THIN-WALL BLACK 1 1/2"ID X 4FT	10 PK
MHSP-1 1/2-2-IIL	HEAT SHRINK THIN-WALL RED 1 1/2"ID X 4FT	10 PK
MHSP-1 1/2-4-IIL	HEAT SHRINK THIN-WALL YELLOW 1 1/2"ID X 4FT	10 PK
MHSP-1 1/2-6-IIL	HEAT SHRINK THIN-WALL BLUE 1 1/2"ID X 4FT	10 PK
MHSP-1 1/2-9-IIL	HEAT SHRINK THIN-WALL CLEAR 1 1/2"ID X 4FT	10 PK
MHSP-1 1/2-WH-IIL	HEAT SHRINK THIN-WALL WHITE 1 1/2"ID X 4FT	10 PK
MHSP-2-0-IIL	HEAT SHRINK THIN-WALL BLACK 2"ID X 4FT	5 PK
MHSP-2-2-IIL	HEAT SHRINK THIN-WALL RED 2"ID X 4FT	5 PK
MHSP-2-5-IIL	HEAT SHRINK THIN-WALL GREEN 2"ID X 4FT	5 PK
MHSP-2-9-IIL	HEAT SHRINK THIN-WALL CLEAR 2"ID X 4FT	5 PK
MHSP-2-WH-IIL	HEAT SHRINK THIN-WALL WHITE 2"ID X 4FT	5 PK
MHSP-3-0-IIL	HEAT SHRINK THIN-WALL BLACK 3"ID X 4FT	5 PK
MHSP-3-9-IIL	HEAT SHRINK THIN-WALL CLEAR 3"ID X 4FT	5 PK
MHSP-4-0-IIL	HEAT SHRINK THIN-WALL BLACK 4"ID X 4FT	5 PK

K-SPEC® HEAT SHRINK TUBING



CROSS-LINK POLYOLEFIN



100 Foot Rolls

- CSA Approved
- Flame Retardant (except Clear)
- Thin Wall 2:1 Ratio
- Oper. Temp.: -49°F to 257°F (-45°C to 125°C)
- Shrink Temp.: Start at 158°F (70°C), recovery at 248°F (120°C)
- Longitudinal shrink ratio: < or = 8%
- 600V rated

Tolerances

3/64"-1/4"	±.008"
5/16"-1/2"	±.012"
5/8"-3/4"	±.016"
5/16"-1/2"	±.012"
3/4"-1"	±.020"

Part No.	DESCRIPTION 100 FOOT SPOOLS	CTN/QTY
MHSP-3/64-0-C	HEAT SHRINK THIN-WALL BLACK 3/64"ID	100' SPL
MHSP-1/16-0-C	HEAT SHRINK THIN-WALL BLACK 1/16"ID	100' SPL
MHSP-3/32-0-C	HEAT SHRINK THIN-WALL BLACK 3/32"ID	100' SPL
MHSP-1/8-0-C	HEAT SHRINK THIN-WALL BLACK 1/8"ID	100' SPL
MHSP-1/4-0-C	HEAT SHRINK THIN-WALL BLACK 1/4"ID	100' SPL
MHSP-1/4-9-C	HEAT SHRINK THIN-WALL CLEAR 1/4"ID	100' SPL
MHSP-3/16-0-C	HEAT SHRINK THIN-WALL BLACK 3/16"ID	100' SPL
MHSP-3/8-0-C	HEAT SHRINK THIN-WALL BLACK 3/8"ID	100' SPL
MHSP-1/2-0-C	HEAT SHRINK THIN-WALL BLACK 1/2"ID	100' SPL
MHSP-1/2-9-C	HEAT SHRINK THIN-WALL BLACK 1/2"ID	100' SPL
MHSP-5/8-0-C	HEAT SHRINK THIN-WALL BLACK 5/8"ID	100' SPL
MHSP-5/8-9-C	HEAT SHRINK THIN-WALL BLACK 5/8"ID	100' SPL
MHSP-3/4-0-C	HEAT SHRINK THIN-WALL BLACK 3/4"ID	100' SPL